

INDUSTRIAL COMPONENT DATA

077682L LEGRAND MO-2USB C+C 1M 15W NM

Brand: LEGRAND | Manufacturer Part Number: 077682L



Manufacturer	LEGRAND
MPN / Reference	077682L
Catalog number	077682L
Category	USB power supply
Minimum order	1 Pcs
Document ID	EO-D02B2D0BC5
Generated	2026-08-01

Product Overview

MO-2USB C+C 1M 15W NM

USB charger base 1 module two ports Type C+C - 3A 15W - Matte black

1mod USB charger base two Type-C+C ports - 3A 15W - Matte black

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LEGRAND > MOSAIC, ARTEOR AND CELIANE MECHANISMS

Additional Product Information

2 USB type C+C charger bases with 1 module. 3A, 15W. For optimal charging of portable devices such as phones, smartphones, MP3 or MP4, speakers, watches, game consoles, powerbanks. 1 module: compact format to save space. Matte black color. Standby consumption 0.1 W. Indoor use. Dimension 45x22.5x41mm. IK04 IP40. Polycarbonate material.

Model Other

Number of USB-A ports 0

Number of USB-C ports 2

Operating voltage 100-240 V

frequency 50-60 Hz

Maximum output current 3000 mA

Output voltage 5-5 V

Power consumption 0.083 W

Connection Method Screw-on terminal

Type of mounting Recessed mounted (plaster)

Colour Black

RAL number 7015
Device width 22.5 mm
Device height 45 mm
Device Depth 41 mm
Min. depth of the recessed box 40 mm
Suitable for protection grade (IP) IP40
Impact resistance IK04
Antibacterial treatment No
Wireless No
Installation Depth 32.5 mm
Operating Temperature 5-40 °C
Storage temperature -20-70 °C
Type of voltage AC
Power Delivery No
USB Power Output 15
Nominal current 0.5-0.5 A
Neutral Mandatory Yes
Display of markings on the connection terminals Yes
Compliant with commissioning tests (1000 V) No
Halogen-free Yes
Number of terminals 2
Terminal capacity 1.5-2.5 mm²
Connection Cable Type Flexible or rigid
Core cross-section 1.5-2.5 mm²
ETIM for 077682L Domestic wiring accessories and controls (EC002949)
Feature Name
Feature Value
Model (EF000010)
Other
Mounting method (EF000003)
Flush mounted
Suitable for degree of protection (IP) (EF006755)
IP40
Connection type (EF0001...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 077682L with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.