

INDUSTRIAL COMPONENT DATA**077690L LEGRAND MO-USB C 1M 20W BL**

Brand: LEGRAND | Manufacturer Part Number: 077690L



Manufacturer	LEGRAND
MPN / Reference	077690L
Catalog number	077690L
Category	USB power supply
Minimum order	10 Pcs
Document ID	EO-04F5519442
Generated	2026-07-31

Product Overview

MO-USB C 1M 20W BL

USB Power Delivery Charger Base 1 Single Port Type C Module - 20W- White

USB Power Delivery 1mod single port Type C charger base - 20W- White

STRUCTURED PRODUCT DATA**Technical Specifications**

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog PathCatalog path **LEGRAND > MOSAIC, ARTEOR AND CELIANE MECHANISMS****Additional Product Information**

1 USB type C charger base with 1 module. 3A, 20W. Power Delivery, for optimal charging of portable devices (tablets, smartphones...) with fast charging function. USB Power Delivery is the new fast charging technology built into iOS/Apple and Android/Google devices. Technology that allows a faster charge level than conventional technologies, working through an exchange between the terminal and the charger. White.Model Other

Number of USB-A ports 0

Number of USB-C ports 1

Operating voltage 100-240 V

frequency 50-60 Hz

Maximum output current 3000 mA

Output voltage 5-12 V

Power consumption 0.048 W

Connection Method Screw-on terminal

Type of mounting Recessed mounted (plaster)

Colour White

RAL number 9003
Device width 22.5 mm
Device height 45 mm
Device Depth 41 mm
Min. depth of the recessed box 40 mm
Suitable for protection grade (IP) IP40
Impact resistance IK04
Antibacterial treatment No
Wireless No
Installation Depth 32.5 mm
Operating Temperature 5-40 °C
Storage temperature -20-70 °C
Type of voltage AC
Power Delivery Yes
USB Power Output 20
Nominal current 0.5-0.5 A
Neutral Mandatory Yes
Display of markings on the connection terminals Yes
Compliant with commissioning tests (1000 V) No
Halogen-free Yes
Number of terminals 2
Terminal capacity 1.5-2.5 mm²
Connection Cable Type Flexible or rigid
Core cross-section 1.5-2.5 mm²
ETIM for 077690L Domestic wiring accessories and controls (EC002949)
Feature Name
Feature Value
Model (EF000010)
Other
Mounting method (EF000003)
Flush mounte...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 077690L with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.