

INDUSTRIAL COMPONENT DATA

077828 LEGRAND SL-INT CREPUSC IK10

Brand: LEGRAND | Manufacturer Part Number: 077828



Manufacturer	LEGRAND
MPN / Reference	077828
Catalog number	077828
Category	Twilight switch
Minimum order	1 Pcs
Document ID	EO-7B4C78269C
Generated	2026-07-31

Product Overview

SL-INT CREPUSC IK10

Twilight switch Soliroc - 1400 W - 400 VA fluorescent - IK 10 - IP 55

Soliroc twilight switch - 1400W - 400VA fluorescent- IK10 - IP55

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LEGRAND > AUTONOMOUS LIGHTING MANAGEMENT

Additional Product Information

Product features

Twilight switch - IP 55 - IK 10 - Power of the light from dusk and off at dawn - Set monobloc with photoelectric cell integrated - 1400 W incandescent - 400 VA fluorescent - brightness Threshold adjustable from 0,5 to 1500 lux General characteristics

Soliroc - other mechanisms - Adapted to the establishments receiving public, places without surveillance, parking, communal areas of the properties - High resistance to shocks IK 10 and to humidity - 4 points for the direct fixation of the plate to the wall and 4 plugs to mount pressure on the plate (removable only by drilling) Mechanisms with front including ETIM for 077828 Domestic wiring accessories and controls (EC000189)

Feature Name

Feature Value

Material (EF002169)

Plastic

Surface finishing (EF006569)

Matt

Halogen free (EF000025)

Yes

Material quality (EF001257)

Thermoplastic

Mounting method (EF000003)

Surface mounted

Nominal voltage (EF000002)

250 V

Transparent (EF006243)

No

Compatible with Apple HomeKit (EF014925)

No

Compatible with Amazon Alexa (EF014927)

No

Compatible with Google Assistant (EF014926)

No

Max. switching current (resistive load) (EF001325)

5.6 A

Surface protection (EF000139)

Untreated

Max. switching power (EF001503)

1400 W

Type of sensor (EF003948)

Built-in light sensor

Switching-off brightness (EF003825)

0.5 lx

Switch-off delay (EF000194)

45 s

Engaging brightness (EF003841)

0.5 lx

Suitable for degree of protection (IP) (EF006755)

IP55

Switching-on delay (EF000193)

45 s

IFTTT support avai...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 077828 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.