

INDUSTRIAL COMPONENT DATA**079190L LEGRAND MO-2USB C+C 2M 15W NM**

Brand: LEGRAND | Manufacturer Part Number: 079190L



Manufacturer	LEGRAND
MPN / Reference	079190L
Catalog number	079190L
Category	USB power supply
Minimum order	1 Pcs
Document ID	EO-89306C3C88
Generated	2026-07-28

Product Overview

MO-2USB C+C 2M 15W NM

USB charger base 2 modules two ports Type C+C - 3A - 15W - Matte black

STRUCTURED PRODUCT DATA**Technical Specifications**

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog PathCatalog path **LEGRAND > MOSAIC, ARTEOR AND CELIANE MECHANISMS****Additional Product Information**

2 USB type C+C charger bases with 2 modules. 3A, 15W. Matte black color. Model Other

Number of USB-A ports 0

Number of USB-C ports 2

Operating voltage 100-240 V

frequency 50-60 Hz

Maximum output current 3000 mA

Output voltage 5-5 V

Power consumption 0.064 W

Connection Method Screw-on terminal

Type of mounting Recessed mounted (plaster)

Colour Black

Device width 45 mm

Device height 45 mm

Device Depth 42 mm

Min. depth of the recessed box 40 mm

Suitable for protection grade (IP) IP40
Impact resistance IK04
Antibacterial treatment No
Wireless No
Installation Depth 33 mm
Operating Temperature 5-40 °C
Storage temperature -20-70 °C
Type of voltage AC
Power Delivery No
USB Power Output 15
Nominal current 0.5-0.5 A
Neutral Mandatory Yes
Display of markings on the connection terminals Yes
Compliant with commissioning tests (1000 V) No
Halogen-free Yes
Number of terminals 2
Terminal capacity 1.5-2.5 mm²
Connection Cable Type Flexible or rigid
Core cross-section 1.5-2.5 mm²
ETIM for 079190L Domestic wiring accessories and controls (EC002949)
Feature Name
Feature Value
Model (EF000010)
Other
Mounting method (EF000003)
Flush mounted
Suitable for degree of protection (IP) (EF006755)
IP40
Connection type (EF000124)
Screwed terminal
Operating voltage (EF003983)
100 V
Device depth (EF008810)
42 mm
Impact strength (EF004293)
IK04
Anti-bacterial treatment (EF023790)
No
Number of ports USB-C (EF017049)
2
Min. depth of built-in installation box (EF012278)
40 mm
Output voltage (EF003933)
5 V
Power....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 079190L with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.