

**INDUSTRIAL COMPONENT DATA****086010L LEGRAND OT-MBL PULS DOUBLE PERS 6A**

Brand: LEGRAND | Manufacturer Part Number: 086010L



|                 |                                    |
|-----------------|------------------------------------|
| Manufacturer    | LEGRAND                            |
| MPN / Reference | 086010L                            |
| Catalog number  | 086010L                            |
| Category        | Venetian blind switch/-push button |
| Minimum order   | 10 Pcs                             |
| Document ID     | EO-022D9D9209                      |
| Generated       | 2026-08-02                         |

**Product Overview**

OT-MBL PULS DOUBLE PERS 6A

Double push button for blinds - Oteo - monobloc - White

**STRUCTURED PRODUCT DATA****Technical Specifications**

No structured technical attributes are currently available. Submit an RFQ for technical review.

**Classification & Catalog Path**Catalog path **LEGRAND > OTEO MECHANISMS****Additional Product Information**

Double Button Mechanism BLIND Square Series Oteo. Shutter controls 6A - Push button for control by means of an automatic box. Oteo - Surface mechanisms - monobloc - IP 31 mechanisms - 250 V~ - White finish RAL 9003.For Venetian blinds Yes

For blinds Yes

For awnings Yes

Type of mounting Base element with full housing, Surface mounted (plaster)

Model 1-pole push button

Number of poles 1

Type of operation Seesaw

With electric lock No

With mechanical latch Yes

Mechanically Driven Yes

Electronically operated No

Material Plastic

Material quality Thermoplastic

Halogen-free Yes  
Surface treatment No treatment  
Surface Finish Bright  
Attachment Type Screw mounting  
Connection Method Plug clamp  
Colour White  
RAL number (similar) 9003  
Transparent No  
Label Space/Print Area Yes  
Suitable for protection grade (IP) IP2X  
Nominal current 6 A  
Nominal Voltage 250 V  
Number of buttons 2  
Number of modules (in case of modular design) 2  
Device width 72 mm  
Device height 72 mm  
Device Depth 31 mm  
Installation Depth 0 mm  
Min. depth of the recessed box 0 mm  
Compatible with Apple HomeKit No  
Compatible with Google Assistant No  
Compatible with Amazon Alexa No  
Compatible IFTTT No  
Impact resistance IK04  
Operating Temperature -5-40 °C  
Storage temperature -5-40 °C  
Type of voltage AC  
frequency 50-60 Hz  
Display of markings on the connection terminals Yes  
Antibacterial treatment No  
Terminal capacity 1.5-1.5 mm<sup>2</sup>  
Connection Cable Type Flexible or rigid  
Core cross-section 1.5-1.5 mm<sup>2</sup>  
Contains battery and/or accumulator No...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 086010L with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.