

**INDUSTRIAL COMPONENT DATA****086067L LEGRAND OT-MBL CONM. 10A+BAS 2P+T 16A**

Brand: LEGRAND | Manufacturer Part Number: 086067L



|                 |                                                      |
|-----------------|------------------------------------------------------|
| Manufacturer    | LEGRAND                                              |
| MPN / Reference | 086067L                                              |
| Catalog number  | 086067L                                              |
| Category        | Combination of switch/push button with socket outlet |
| Minimum order   | 5 Pcs                                                |
| Document ID     | EO-11441E5B7E                                        |
| Generated       | 2026-07-29                                           |

**Product Overview**

OT-MBL CONM. 10A+BAS 2P+T 16A

10AX Switch + Base 2P+T 16A - 250V~ - Oteo - monobloc - White

**STRUCTURED PRODUCT DATA****Technical Specifications**

No structured technical attributes are currently available. Submit an RFQ for technical review.

**Classification & Catalog Path**Catalog path **LEGRAND > OTEO MECHANISMS****Additional Product Information**

Mechanism Switch + 2 pole socket + side ground Square series Oteo. Double mechanisms - 10 AX switch - 250V~ - Base 2P+T 16A - 250V~ - with child protection shutters. Oteo - Surface mechanisms - monobloc - IP 31 mechanisms - 250V~ - White finish RAL 9003.Switch/Push Button Type Bidirectional switch

Neutral Conductor Coupling No

Wall plug version Power socket with protective contact CEE 7/3 (type F)

Number of sockets 1

Type of operation Rocker/button

Assembly Direction Horizontal and vertical

Attachment Type Screw mounting

With light No

Type of mounting Surface mounted (plaster)

Material Plastic

Material quality Thermoplastic

Halogen-free Yes

Surface treatment No treatment

Surface Finish Bright  
Colour White  
RAL number (similar) 9003  
Transparent No  
Suitable for protection grade (IP) IP20  
Nominal Voltage 230 V  
Nominal outlet current 16 A  
Nominal current 16 A  
Surge protection No  
Residual Current Device No  
With microfusion No  
Number of active (round) contacts 1  
Number of active contacts (drawings) 0  
Min. depth of the recessed box 0 mm  
Device width 72 mm  
Device height 136 mm  
Device Depth 42 mm  
Compatible with Apple HomeKit No  
Compatible with Google Assistant No  
Compatible with Amazon Alexa No  
Compatible IFTTT No  
Installation Depth 0 mm  
Impact resistance IK04  
Operating Temperature -5-40 °C  
Storage temperature -5-40 °C  
Type of voltage AC  
Display of markings on the connection terminals Yes  
Antibacterial treatment No  
Prewired No  
Connection Method Other  
Terminal capacity 1.5-2.5 mm<sup>2</sup>  
Con...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 086067L with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.