

INDUSTRIAL COMPONENT DATA**088064 LEGRAND BOX GROUND IP66 LID/BIS IN**

Brand: LEGRAND | Manufacturer Part Number: 088064



Manufacturer	LEGRAND
MPN / Reference	088064
Catalog number	088064
Category	Installation box for underfloor-installation
Minimum order	1 Pcs
Document ID	EO-5556192E35
Generated	2026-07-29

Product Overview

BOX GROUND IP66 LID/BIS IN

Legrand IP66 Floor Box with Hinged Lid 170mm

Floor box with lid hinged lid - IP66 - 4mod - Inox

STRUCTURED PRODUCT DATA**Technical Specifications**

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog PathCatalog path **LEGRAND > COLUMN WIRING MANAGEMENT****Additional Product Information**

Supplied with lid and 4 module support frame for Arteor modules To be installed in flush mounting back box Cat.No. 0880 69 or directly in raised floor Overall Ø 170 mm IK 09 with the lid closed Resistance to loads with lid closed: 10000 N Cover model Round

Number of inlets 1

Number of device cups 1

Number of socket outlets with protective contact CEE 7/3 (type F) 0

Number of CEE socket outlets (IEC 60309) 16 A / 400 V / 5P (1, 2, 3, N, PE) 0

Number of CEE socket outlets (IEC 60309) 32 A / 400 V / 5P (1, 2, 3, N, PE) 0

Number of socket outlets British Standard BS 1363 0

With cable outlet in cover No

Lockable cover Yes

Lock control Other

Housing material Other

Surface protection housing Chromium-plated

Material cover Other
Surface protection cover Other
Surface treatment cover Other
Degree of protection (IP) when in use (cable outlet open) Other
With opening carpeting No
Depth of flooring recess 0 mm
Protective frame carpeting Yes
Colour Other
Suitable for indoor installation Yes
Suitable for outdoor installation No
Suitable for subfloor duct Yes
Suitable for hollow floor Yes
Suitable for double floor built-in Yes
Suitable for concrete installation Yes
Suitable for floors in computer rooms Yes
Suitable for wet cleaning No
Outer diameter 170 mm
Built-in diameter 152 mm
Min. built-in depth 65 mm
Depth 70 mm
number of rows 1
degree of impact strength (IK) IK09
Operating / setting temperature -5-60 °C
Halogen free Yes
Fitted with USB plug No
ETIM for 088064 Underfloor trunking and....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 088064 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.