

INDUSTRIAL COMPONENT DATA

090472 LEGRAND TAKING GREEN UP ACCES TO 3.2 KVA

Brand: LEGRAND | Manufacturer Part Number: 090472



Manufacturer	LEGRAND
MPN / Reference	090472
Catalog number	090472
Category	GREEN'UPP SOCKETS AND BASES
Minimum order	1 unit
Document ID	EO-249F65DA09
Generated	2026-08-03

Product Overview

090472 LEGRAND TAKING GREEN UP ACCES TO 3.2 KVA

STRUCTURED PRODUCT DATA

Technical Specifications

TECHNICAL ATTRIBUTE	VALUE
Cross section of the power contacts (EF009329)	6 mm ²
LED integrated (EF009328)	No
Height (EF000040)	147.5 mm
Model (EF000010)	Charging socket outlet
Degree of protection (IP) (EF005474)	Other
Number of communication contacts (EF009325)	3
Type of current (EF000143)	AC single phase
With access interlocking (EF009324)	No
Length of the fixed connection cable (EF009327)	50 m
Nominal voltage (EF000002)	250 V
Max. nominal current (EF009326)	16 A
With interlocking actuator (EF009323)	No
Standard (EF009322)	Other
Depth (EF000049)	76 mm
Width (EF000008)	180 mm
Connection system (EF002649)	Screw connection

Classification & Catalog Path

Catalog path

LEGRAND > GREEN'UPP SOCKETS AND BASES

Additional Product Information

Energy efficiency solution

Pack (number of units)1

Volume (dm³)4.047

Weight (g)470.00

Product characteristicsMode 1 and Mode 2 sockets - 16 A EV

Heavy-duty mechanisms with silvered contacts

Single-phase sockets - screw connection - 230 V

Supplied with base Cat.No 0 904 78 for hanging up the vehicle charging cable control box

For charging 1 vehicle

Conform to IEC 60-884-1

IP 55 - IK 08 surface-mounting

Suitable for installation in private houses

Plastic socket with flap cover

Supplied complete with surface mounting box fitted with an ISO 20 cable gland

Dimensions (H x W x D): 98 x 98 x 70 mm (exc. cable gland)

German standard socket outlet

General characteristicsGreen'up™ Access sockets 16 A - 230 V - 16 A EV - for electric vehiclesUsed for safely charging rechargeable electric and hybrid vehicles which take Mode 2 cord (compatible with Mode 1)

Connected to the consumer panel via one 3 x 2.5 mm² dedicated line (1 line per socket) protected by 30 mA - 20 A C curve, type A or Hpi RCBO (or 30 mA type A or HPI RCCB + 20 A C curve circuit breaker)

Recommended installation height: 1.30 m f...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 090472 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.