

INDUSTRIAL COMPONENT DATA

146636 LEGRAND Stabilised switched modules power supply three-phase 960 W output 24 V 960 W. Switched-mode d..

Brand: LEGRAND | Manufacturer Part Number: 146636



Manufacturer	LEGRAND
MPN / Reference	146636
Catalog number	146636
Category	INDUSTRIAL VARIOUS CONTROL
Minimum order	1 unit
Document ID	EO-0D9EA43B4A
Generated	2026-08-04

Product Overview

146636 LEGRAND Stabilised switched modules power supply three-phase 960 W output 24 V 960 W. Switched-mode d..

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	LEGRAND > INDUSTRIAL VARIOUS CONTROL
--------------	--------------------------------------

Additional Product Information

Description

Switched-mode direct current power supply with stabilized 24VDC output adjustable via front potentiometer. Three-phase 960W unit with integrated PFC filter, short-circuit and overload protection.

Product characteristics

Stabilised switched mode power supplies - single/two - phase and three - phase - Conforming to standards UL 508, IEC EN 60950 - 1 and IEC EN 61204 - 3 - UL - approved in USA (and Canada for Cat. Nos. 1 466 54/63/82) - Operating frequency : 50/60 Hz - Output voltage present indicator - Potentiometer for adjusting the output voltage on front panel - Integrated short - circuit and overload protection - With signal or relay contact for feedback on the status of the active output voltage - Connection with copper conductors only - For mounting on a symmetrical rail depth 7.5 mm and 15 mm

Three - phase 960 W - Operation possible on 2 phases (80% of the Nominal power) - Low harmonic pollution due to the integrated PFC filter - Adjustable output voltage - Aluminium casing
Input voltage : 3 x 380 to 500 V~ Output voltage : 24 V= - Nominal power : 960 W - Nominal rating : 40 A - Setting range : 24 to 28 V - Width : 110 mm

Technical characteristics

Voltage type (supply voltage) AC/DC

1st secondary output voltage (Min-Max) 24-48 V

Max. output current 1 40 A
Secondary voltage adjustable Yes
Nominal value output voltage 1 48 V
Nominal value output current 1 40 A
Short-circuit-proof Yes
Rated supply voltage AC 50 Hz (Min-Max) 380-500 V
Output voltage stabilized Yes...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 146636 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.