

INDUSTRIAL COMPONENT DATA

402056 LEGRAND DIFFERENTIAL HOUSING 2/25/30MA

Brand: LEGRAND | Manufacturer Part Number: 402056



Manufacturer	LEGRAND
MPN / Reference	402056
Catalog number	402056
Category	Residual current circuit breaker (RCCB)
Minimum order	5 Pcs
Document ID	EO-719CF4EDE4
Generated	2026-07-29

Product Overview

DIFFERENTIAL HOUSING 2/25/30MA

Differential RX3 - 2P - 230 V~ - 30 mA - 25 A - type AC

RX³ Differential - 2P - 230V~ - 30mA- 25A - AC Type

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LEGRAND > HOME CIRCUIT BREAKERS

Additional Product Information

Product features

Circuit breakers two-pole 230 V~ - 30mA - domestic Installations -captive Screws-head - mixed Neutral-to-the-left Type AC -

Sensitivity: 30 mA - In: 25 - Number of modules: 2 General characteristics

Circuit breakers RX3 from 25 To 40 A - types AC and A - According to UNE en 61008-2-1 - Allow feeding by comb - Type

AC: detection of failures of components AC - Type A: fault detection of AC components and DC - do Not accept auxiliary -

Capacity embornamiento: 25mm² flexible/35mm² rigid

ETIM for 402056 Circuit breakers and fuses (EC000003)

Feature Name

Feature Value

Explosion-proof (EF004663)

No

Connectable conductor cross section solid-core (EF007337)

0.75 mm²

Frequency (EF005455)

50 Hz
Selective protection (EF002561)
No
Short-circuit breaking capacity (I_{cw}) (EF002562)
10 kA
Ambient temperature during operating (EF007515)
-25 °C
Degree of protection (IP) (EF005474)
IP20
Leakage current type (EF002560)
AC
Voltage type (EF000187)
AC
Additional equipment possible (EF008148)
No
Mounting method (EF000003)
DIN rail
Surge current capacity (EF002564)
0.25 kA
Number of poles (EF001391)
2
Short-time delayed tripping (EF003604)
No
Rated fault current (EF002358)
0.03 A
Rated impulse withstand voltage U_{imp} (EF011980)
4 kV
Built-in depth (EF000218)
44 mm
RAL-number (similar) (EF003882)
7035
Pollution degree (EF002570)
2
Width in number of modular spacings (EF002950)
2
Rated insulation voltage U_i (EF001366)
250 V
With interlocking device (EF007385)
Yes
Connectable conductor c...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 402056 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.