

INDUSTRIAL COMPONENT DATA

402059 LEGRAND A DIFFERE. HOUSING 2/25/30MA

Brand: LEGRAND | Manufacturer Part Number: 402059



Manufacturer	LEGRAND
MPN / Reference	402059
Catalog number	402059
Category	Residual current circuit breaker (RCCB)
Minimum order	5 Pcs
Document ID	EO-B56977524E
Generated	2026-07-29

Product Overview

A DIFFERE. HOUSING 2/25/30MA

Differential RX3 - 2P - 230 V~ - 30 mA - 25 A - Type To

RX3 Differential - 2P - 230V~ - 30mA- 25A - TypeA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LEGRAND > HOME CIRCUIT BREAKERS

Additional Product Information

Product features

Circuit breakers two-pole 230 V~ - 30mA - domestic Installations -captive Screws-head - mixed Neutral-to-left-Type A -

Sensitivity: 30 mA - In: 25 - Number of modules: 2 General characteristics

Circuit breakers RX3 from 25 To 40 A - types AC and A - According to UNE en 61008-2-1 - Allow feeding by comb - Type

AC: detection of failures of components AC - Type A: fault detection of AC components and DC - do Not accept auxiliary -

Capacity embornamiento: 25mm2 flexible/35mm2 rigid

ETIM for 402059 Circuit breakers and fuses (EC000003)

Feature Name

Feature Value

Explosion-proof (EF004663)

No

Connectable conductor cross section solid-core (EF007337)

0.75 mm²

Frequency (EF005455)

50 Hz
Selective protection (EF002561)
No
Short-circuit breaking capacity (I_{cw}) (EF002562)
10 kA
Ambient temperature during operating (EF007515)
-25 °C
Degree of protection (IP) (EF005474)
IP20
Leakage current type (EF002560)
A
Voltage type (EF000187)
AC
Additional equipment possible (EF008148)
No
Mounting method (EF000003)
DIN rail
Surge current capacity (EF002564)
0.25 kA
Number of poles (EF001391)
2
Short-time delayed tripping (EF003604)
No
Rated fault current (EF002358)
0.03 A
Rated impulse withstand voltage U_{imp} (EF011980)
4 kV
Built-in depth (EF000218)
44 mm
RAL-number (similar) (EF003882)
7035
Pollution degree (EF002570)
2
Width in number of modular spacings (EF002950)
2
Rated insulation voltage U_i (EF001366)
250 V
With interlocking device (EF007385)
Yes
Connectable conductor cross s...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 402059 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.