

INDUSTRIAL COMPONENT DATA

403005 LEGRAND DIFFERENTIAL TX3 4/40/30 AC

Brand: LEGRAND | Manufacturer Part Number: 403005



Manufacturer	LEGRAND
MPN / Reference	403005
Catalog number	403005
Category	Residual current circuit breaker (RCCB)
Minimum order	1 Pcs
Document ID	EO-D0DBB31376
Generated	2026-07-29

Product Overview

DIFFERENTIAL TX3 4/40/30 AC

RCCB TX³ - 4P 400 V~ - 30 mA - 40 A - AC type - neutral on left-hand - no aux.Differential TX³ 4/40/30 alternating current

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LEGRAND > TERTIARY CIRCUIT BREAKERS

Additional Product Information

Pack (number of units)1

Volume (dm3)0.701

Weight (g)333.00

Product characteristics4-pole - 400 V~

Neutral on left-hand side

AC type

Sensitivity : 30 mA

In : 40 A

Number of modules : 4

General characteristicsRCCBs TX³ - residual current circuit breakers - from 25 A to 63 A - AC and A typesConform to IEC 61008-1

Compatible with prong-type supply busbars

AC type : detect AC component faults

A type : detect AC and DC component faults

Do not accept auxiliaries

ETIM for 403005 Circuit breakers and fuses (EC000003)

Feature Name

Feature Value

Explosion-proof (EF004663)

No

Connectable conductor cross section solid-core (EF007337)

0.75 mm²

Frequency (EF005455)

50 Hz

Selective protection (EF002561)

No

Short-circuit breaking capacity (I_{cn}) (EF002562)

10 kA

Ambient temperature during operating (EF007515)

-25 °C

Degree of protection (IP) (EF005474)

IP20

Leakage current type (EF002560)

AC

Voltage type (EF000187)

AC

Additional equipment possible (EF008148)

No

Mounting method (EF000003)

DIN rail

Surge current capacity (EF002564)

0.25 kA

Number of poles (EF001391)

4

Short-time delayed tripping (EF003604)

No

Rated fault current (EF002358)

0.03 A

Rated impulse withstand voltage U_{imp} (EF011980)

4 kV

Built-in depth (EF000218)

44 mm

RAL-number (similar) (EF003882)

7035

Pollution degree (EF002570)

2

Width in number of modular spacings (EF002950)

4

Rated insulation voltage U_i (EF001366)

500 V

With interlocking device (EF007385)

Yes

Connectable conductor cross section multi-wired (EF007343)

0.75 mm²....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 403005 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.