

INDUSTRIAL COMPONENT DATA

403032 LEGRAND DIFFERENTIAL TX3 2/25/30 AC

Brand: LEGRAND | Manufacturer Part Number: 403032



Manufacturer	LEGRAND
MPN / Reference	403032
Catalog number	403032
Category	Residual current circuit breaker (RCCB)
Minimum order	1 Pcs
Document ID	EO-6B1A990B06
Generated	2026-07-28

Product Overview

DIFFERENTIAL TX3 2/25/30 AC

Differential TX3 - 2P - 230 V~ - 30 mA - 25 A - type AC

TX3 Differential - 2P - 230V~ - 30mA- 25A - AC Type

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LEGRAND > TERTIARY CIRCUIT BREAKERS

Additional Product Information

Product features

Circuit breakers two-pole 230 V~ - 30mA Type AC - Sensitivity: 30 mA - In: 25 - Number of modules: 2 General characteristics

Circuit breakers TX3 25-To 40 - types AC - According to UNE en 61008-1 - Let the power combs - Portaetiquetas built-in - Type BC: fault detection of AC components - you do Not accept auxiliary - Capacity embornamiento: 25mm2 flexible/35mm2 rigid

ETIM for 403032 Circuit breakers and fuses (EC000003)

Feature Name

Feature Value

Explosion-proof (EF004663)

No

Connectable conductor cross section solid-core (EF007337)

0.75 mm²

Frequency (EF005455)

50 Hz
Selective protection (EF002561)
No
Short-circuit breaking capacity (I_{cw}) (EF002562)
10 kA
Ambient temperature during operating (EF007515)
-25 °C
Degree of protection (IP) (EF005474)
IP20
Leakage current type (EF002560)
AC
Voltage type (EF000187)
AC
Additional equipment possible (EF008148)
No
Mounting method (EF000003)
DIN rail
Surge current capacity (EF002564)
0.25 kA
Number of poles (EF001391)
2
Short-time delayed tripping (EF003604)
No
Rated fault current (EF002358)
0.03 A
Rated impulse withstand voltage U_{imp} (EF011980)
4 kV
Built-in depth (EF000218)
44 mm
RAL-number (similar) (EF003882)
7035
Pollution degree (EF002570)
2
Width in number of modular spacings (EF002950)
2
Rated insulation voltage U_i (EF001366)
250 V
With interlocking device (EF007385)
Yes
Connectable conductor cross section multi-wired (EF007343)
0.75 mm²
Rated current (EF000227)
25 A
Rated voltage (EF000228)
230 V

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 403032 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.