

INDUSTRIAL COMPONENT DATA

403036 LEGRAND DIFFERENTIAL TX3 2/40/30 A

Brand: LEGRAND | Manufacturer Part Number: 403036



Manufacturer	LEGRAND
MPN / Reference	403036
Catalog number	403036
Category	Residual current circuit breaker (RCCB)
Minimum order	1 Pcs
Document ID	EO-927C532F31
Generated	2026-07-29

Product Overview

DIFFERENTIAL TX3 2/40/30 A

RCCB TX³ - 2P 230 V~ - 30 mA - 40 A - A type - do not accept auxiliariesTX³ Differential - 2P - 230V~ - 30mA- 40A - Type A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LEGRAND > TERTIARY CIRCUIT BREAKERS

Additional Product Information

Pack (number of units)1

Volume (dm3)0.381

Weight (g)238.00

Product characteristics2-pole - 230 V~

A type

Sensitivity : 30 mA

In : 40 A

Number of modules : 2

General characteristicsRCCBs TX³ - residual current circuit breakers - from 25 A to 63 A - AC and A typesConform to IEC 61008-1

Compatible with prong-type supply busbars

AC type : detect AC component faults

A type : detect AC and DC component faults

Do not accept auxiliaries

ETIM for 403036 Circuit breakers and fuses (EC000003)

Feature Name

Feature Value

Explosion-proof (EF004663)

No

Connectable conductor cross section solid-core (EF007337)

0.75 mm²

Frequency (EF005455)

50 Hz

Selective protection (EF002561)

No

Short-circuit breaking capacity (I_{cn}) (EF002562)

10 kA

Ambient temperature during operating (EF007515)

-25 °C

Degree of protection (IP) (EF005474)

IP20

Leakage current type (EF002560)

A

Voltage type (EF000187)

AC

Additional equipment possible (EF008148)

No

Mounting method (EF000003)

DIN rail

Surge current capacity (EF002564)

0.25 kA

Number of poles (EF001391)

2

Short-time delayed tripping (EF003604)

No

Rated fault current (EF002358)

0.03 A

Rated impulse withstand voltage U_{imp} (EF011980)

4 kV

Built-in depth (EF000218)

44 mm

RAL-number (similar) (EF003882)

7035

Pollution degree (EF002570)

2

Width in number of modular spacings (EF002950)

2

Rated insulation voltage U_i (EF001366)

250 V

With interlocking device (EF007385)

Yes

Connectable conductor cross section multi-wired (EF007343)

0.75 mm²

Rated current (EF000227)

40....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 403036 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.