

INDUSTRIAL COMPONENT DATA

403615 LEGRAND MAGNET TX3 6KA C 3P 10A

Brand: LEGRAND | Manufacturer Part Number: 403615



Manufacturer	LEGRAND
MPN / Reference	403615
Catalog number	403615
Category	Miniature circuit breaker (MCB)
Minimum order	1 Pcs
Document ID	EO-D6B27D461A
Generated	2026-07-31

Product Overview

MAGNET TX3 6KA C 3P 10A
MCB TX³ 6000 - 3P 400 V~ - 10 A - C curve - prong-type supply busbars
TX³ Circuit Breaker - 3P - 400V~ - 10A - C curve - 3mod

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LEGRAND > TERTIARY CIRCUIT BREAKERS

Additional Product Information

Pack (number of units)1
Volume (dm3)0.521
Weight (g)312.00
Product characteristics3-pole 400 V~
C curve
Nominal rating I_n : 10 A
Number of modules : 3
General characteristicsMCBs TX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curveConform to IEC 60898-1
Compatible with prong-type supply busbars
Breaking capacity:6000 - IEC 60898-1 - 230/400 V~
6 kA - IEC 60947-2 - 230/400 V~
Can be equipped with DX³ signalling and remote tripping auxiliaries and motorised controls
Do not accept add-on modules
ETIM for 403615 Circuit breakers and fuses (EC000042)

Feature Name

Feature Value

Explosion-proof (EF004663)

No

Degree of protection (IP) (EF005474)

IP20

Rated short-circuit breaking capacity I_{cn} according to EN 60898 at 230 V (EF009556)

10 kA

Concurrently switching neutral conductor (EF005997)

No

Voltage type (EF000187)

AC

Rated short-circuit breaking capacity I_{cn} according to EN 60898 at 400 V (EF009555)

6 kA

Additional equipment possible (EF008148)

Yes

Rated short-circuit breaking capacity I_{cu} according to IEC 60947-2 at 400 V (EF009558)

6 kA

Rated short-circuit breaking capacity I_{cu} according to IEC 60947-2 at 230 V (EF009557)

10 kA

Rated impulse withstand voltage U_{imp} (EF011980)

4 kV

Number of protected poles (EF005548)

3

Frequency (EF000416)

50 Hz

Built-in depth (EF000218)

44 mm

Number of poles (total) (EF008618)

3

Pollution degree (EF002570)

2

Width in number of modular spacings (EF002950)

3

Rated insulation voltage U_i (EF001366)

500 V

Rated current (EF000227)

10 A

Current...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 403615 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.