

**INDUSTRIAL COMPONENT DATA****403620 LEGRAND MAGNET TX3 6KA C 3P 40A**

Brand: LEGRAND | Manufacturer Part Number: 403620



|                 |                                 |
|-----------------|---------------------------------|
| Manufacturer    | LEGRAND                         |
| MPN / Reference | 403620                          |
| Catalog number  | 403620                          |
| Category        | Miniature circuit breaker (MCB) |
| Minimum order   | 1 Pcs                           |
| Document ID     | EO-35AB83E011                   |
| Generated       | 2026-08-02                      |

**Product Overview**

MAGNET TX3 6KA C 3P 40A

MCB TX<sup>3</sup> 6000 - 3P 400 V~ - 40 A - C curve - prong-type supply busbarsTX<sup>3</sup> Circuit Breaker - 3P - 400V~ - 40A - C curve - 3mod**STRUCTURED PRODUCT DATA****Technical Specifications**

No structured technical attributes are currently available. Submit an RFQ for technical review.

**Classification & Catalog Path**Catalog path **LEGRAND > TERTIARY CIRCUIT BREAKERS****Additional Product Information**

Pack (number of units)1

Volume (dm<sup>3</sup>)0.521

Weight (g)403.00

Product characteristics3-pole 400 V~

C curve

Nominal rating I<sub>n</sub> : 40 A

Number of modules : 3

General characteristicsMCBs TX<sup>3</sup> 6000 - thermal magnetic MCBs from 6 A to 63 A - C curveConform to IEC 60898-1

Compatible with prong-type supply busbars

Breaking capacity:6000 - IEC 60898-1 - 230/400 V~

6 kA - IEC 60947-2 - 230/400 V~

Can be equipped with DX<sup>3</sup> signalling and remote tripping auxiliaries and motorised controls

Do not accept add-on modules

ETIM for 403620 Circuit breakers and fuses (EC000042)

Feature Name

Feature Value

Explosion-proof (EF004663)

No

Degree of protection (IP) (EF005474)

IP20

Rated short-circuit breaking capacity  $I_{cn}$  according to EN 60898 at 230 V (EF009556)

10 kA

Concurrently switching neutral conductor (EF005997)

No

Voltage type (EF000187)

AC

Rated short-circuit breaking capacity  $I_{cn}$  according to EN 60898 at 400 V (EF009555)

6 kA

Additional equipment possible (EF008148)

Yes

Rated short-circuit breaking capacity  $I_{cu}$  according to IEC 60947-2 at 400 V (EF009558)

6 kA

Rated short-circuit breaking capacity  $I_{cu}$  according to IEC 60947-2 at 230 V (EF009557)

10 kA

Rated impulse withstand voltage  $U_{imp}$  (EF011980)

4 kV

Number of protected poles (EF005548)

3

Frequency (EF000416)

50 Hz

Built-in depth (EF000218)

44 mm

Number of poles (total) (EF008618)

3

Pollution degree (EF002570)

2

Width in number of modular spacings (EF002950)

3

Rated insulation voltage  $U_i$  (EF001366)

500 V

Rated current (EF000227)

40 A

Current...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 403620 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.