

INDUSTRIAL COMPONENT DATA

404937 LEGRAND COMB UNIPOLAR 57 MOD

Brand: LEGRAND | Manufacturer Part Number: 404937



Manufacturer	LEGRAND
MPN / Reference	404937
Catalog number	404937
Category	Phase busbar
Minimum order	10 Pcs
Document ID	EO-46E83AF92B
Generated	2026-07-29

Product Overview

COMB UNIPOLAR 57 MOD

Legrand Insulated Busbar 57 Way 1 Pole Units

Universal unipolar feeding comb - L. 1m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	LEGRAND > SPLITTERS
--------------	---------------------

Additional Product Information

Supply busbars For 57 single pole units1 Reversible blue/blackDepth 4 mm

Number of phases 1

Number of poles 1

Suitable for number of devices 57

Module width 17.7 mm

Cross section 16 mm²

Length 1008 mm

Can be cut to size Yes

Width in number of modular spacings 57

Rated permanent current I_u 63 A

Type of electric connection Pin

Insulated Yes

Rated surge voltage 2 kV

Conditioned rated short-circuit current I_q 0.63 kA

Max. rated operation voltage Ue 400 V
Rated short-time withstand current Icw 1.92 kA
Suitable for devices with N-conductor Yes
Suitable for devices with auxiliary switch No
Colour Other
Height 21 mm
Operating / setting temperature -20-50 °C
Storage temperature -40-70 °C
Busbar type supplied Horizontal
ETIM for 404937 Low-voltage industrial controls and switchgear (EC000215)
Feature Name
Feature Value
Suitable for devices with auxiliary switch (EF007217)
No
Suitable for devices with N-conductor (EF007218)
Yes
Module width (EF007504)
17.7 mm
Number of phases (EF000351)
1
Width in number of modular spacings (EF002950)
57
Conditioned rated short-circuit current Iq (EF001444)
0.63 kA
Max. rated operation voltage Ue (EF007357)
400 V
Rated permanent current Iu (EF001389)
63 A
Rated surge voltage (EF002993)
2 kV
Type of electric connection (EF003961)
Pin
Suitable for number of devices (EF007241)
57
Rated short-time withstand current Icw (EF007050)
1.92 kA
Number of poles (EF001391)
1
Colour (EF000007)
Other
Can be cut to size (EF015250)
Yes
Insulated (EF000019)
Yes
Length (...)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 404937 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.