

INDUSTRIAL COMPONENT DATA

405034 LEGRAND REPAR VERT TETRAPOLAR 125A 4R

Brand: LEGRAND | Manufacturer Part Number: 405034



Manufacturer	LEGRAND
MPN / Reference	405034
Catalog number	405034
Category	Phase busbar
Minimum order	1 Pcs
Document ID	EO-24E75FFF17
Generated	2026-08-02

Product Overview

REPAR VERT TETRAPOLAR 125A 4R

Combs vertical VX3 auto - 125 - case 4 rows

VX³ auto vertical combs - 125A for 4-row boxes

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	LEGRAND > SPLITTERS
--------------	---------------------

Additional Product Information

Product features

Combs vertical 125 TO VX3 self - Assembling in the boxes XL3 160, XL3 400 - Capacity of the terminals: - power supply: 16 to 35 mm² (flexible)/50 mm² (rigid) - outputs: 6 to 16 mm² (flexible or rigid) - box 4 row - Height: 506 mm - 6 outputs per phase (x3) + 9 outputs neutral General characteristics

Vertical distribution VX3 auto 63 and 125 A - combs tetrapolares with terminals automatic - Combs tetrapolares IP XXB equipped with terminal output auto - Enable sharing by flexible wires with or without leading - Feeding through the top or bottom terminals with screws - which Include seals for the terminals of power is not used and locking legs for side-mount in the boxes - Not to make any intervention under tension

ETIM for 405034 Low-voltage industrial controls and switchgear (EC000215)

Feature Name

Feature Value

Suitable for devices with auxiliary switch (EF007217)

No

Suitable for devices with N-conductor (EF007218)

Yes

Module width (EF007504)

150 mm

Number of phases (EF000351)

3

Conditioned rated short-circuit current I_q (EF001444)

0.63 kA

Max. rated operation voltage U_e (EF007357)

400 V

Rated permanent current I_u (EF001389)

125 A

Rated surge voltage (EF002993)

2 kV

Type of electric connection (EF003961)

Other

Suitable for number of devices (EF007241)

6

Rated short-time withstand current I_{cw} (EF007050)

6 kA

Number of poles (EF001391)

27

Colour (EF000007)

Other

Can be cut to size (EF015250)

No

Insulated (EF000019)

Yes

Length (EF001438)

506 mm

Cross section (E...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 405034 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.