

INDUSTRIAL COMPONENT DATA

406286 LEGRAND COIL DISCONNECT POP

Brand: LEGRAND | Manufacturer Part Number: 406286



Manufacturer	LEGRAND
MPN / Reference	406286
Catalog number	406286
Category	Auxiliary device for distribution board devices
Minimum order	1 Pcs
Document ID	EO-7A66A3E85B
Generated	2026-07-31

Product Overview

COIL DISCONNECT POP

Power overvoltage protection (POP) DX³ - 275 V - 1 moduleVoltage threshold trigger "POP" - DX³ - threshold at 275 V~

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LEGRAND > TERTIARY CIRCUIT BREAKERS

Additional Product Information

Pack (number of units)1

Volume (dm³)0.219

Weight (g)74.00

Product characteristicsRemote tripping auxiliaries

To fit on the left-hand side of DX³ and TX³ devices

Maximum 1 remote tripping auxiliary per device

Allow insertion of the supply busbar

No tool required for joining together the auxiliary and the main device.

For MCBs, RCBOs, RCCBs and remote trip isolating switches

Power overvoltage protection (POP)

Protects the circuit by tripping its associated device in case of overvoltage between phase and neutral.

Tripping threshold : 275 V (eg. in case of neutral interruption)

Protects the circuit by tripping its associated device in case of overvoltage between phase and neutral.

Tripping threshold : 275 V (eg. in case of neutral interruption)

Number of modules : 1

General characteristics Signalling, remote tripping auxiliaries and motorised controls DX³

ETIM for 406286 Modular devices for distribution board/surface mounting (EC001286)

Feature Name

Feature Value

Function (EF000030)

Shunt release (for power circuit breaker)

Number of fault-signal switches (EF007613)

0

Number of contacts as change-over contact (EF008257)

0

Width in number of modular spacings (EF002950)

1

Suitable for max. current main contact unit (EF008730)

125 A

Voltage type (EF000187)

AC

Number of contacts as normally closed contact (EF008255)

0

Number of contacts as normally open contact (EF008256)

0

With auto test for earth leakage function (EF008727)

No

Rated voltage (EF000228)

230 V

Device fitting (EF007826...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 406286 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.