INDUSTRIAL COMPONENT DATA

407803 LEGRAND MAGNET DX3 6/10 KA C 2P 32A

Brand: LEGRAND | Manufacturer Part Number: 407803

Manufacturer	**LEGRAND**
MPN / Reference	**407803**
Catalog number	**407803**
Category	**Miniature circuit breaker (MCB)**
Minimum order	**5 Pcs**
Document ID	**EO-E1B3CB4DF9**
Generated	**2026-08-03**

Product Overview

MAGNET DX3 6/10 KA C 2P 32A
MCB - DX³ 6000 - 10 kA - 2P - 230/400 V~ - 32 A - C curve
DX³ 6000/10kA Circuit Breaker - 2P - 230/400V~ - 32A - C curve

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	**LEGRAND > TERTIARY CIRCUIT BREAKERS**

Additional Product Information

Pack (number of units)5
Volume (dm3)1.619
Weight (g)1 428.00
Product characteristics2-pole 230/400 V~
C curve
Nominal rating In : 32 A
Number of modules : 2
General characteristicsMCBs DX³ 6000 - 10 kA - thermal magnetic circuit breakers from 1 A to 63 A - B and C curvesConform to IEC 60898-1
Compatible with both, prong-type and fork type supply busbars
Breaking capacity
6000 - IEC 60898-1 - 400 V~
10 kA - IEC 60947-2 - 400 V~
Can be equipped with DX³ signalling and remote tripping auxiliaries, motorised controls and add-on modules

ETIM for 407803 Circuit breakers and fuses (EC000042)
Feature Name
Feature Value
Explosion-proof (EF004663)
No
Connectable conductor cross section solid-core (EF007337)
1.5 mm²
Ambient temperature during operating (EF007515)
-25 °C
Degree of protection (IP) (EF005474)
IP20
Concurrently switching neutral conductor (EF005997)
No
Voltage type (EF000187)
AC
Rated short-circuit breaking capacity Icn according to EN 60898 at 400 V (EF009555)
6 kA
Additional equipment possible (EF008148)
Yes
Rated short-circuit breaking capacity Icu according to IEC 60947-2 at 400 V (EF009558)
10 kA
Rated short-circuit breaking capacity Icu according to IEC 60947-2 at 230 V (EF009557)
25 kA
Rated impulse withstand voltage Uimp (EF011980)
4 kV
Number of protected poles (EF005548)
2
Frequency (EF000416)
50 Hz
Built-in depth (EF000218)
44 mm
Number of poles (total) (EF008618)
2
Pollution degree (EF002570)
2
Width in number of modular spacings (EF002950)
2
Rated insulation v...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 407803 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.