

**INDUSTRIAL COMPONENT DATA**

# 408150 LEGRAND MAGNET DX3 6/10 KA D 4P 32A

Brand: LEGRAND | Manufacturer Part Number: 408150



|                 |                                 |
|-----------------|---------------------------------|
| Manufacturer    | LEGRAND                         |
| MPN / Reference | 408150                          |
| Catalog number  | 408150                          |
| Category        | Miniature circuit breaker (MCB) |
| Minimum order   | 1 Pcs                           |
| Document ID     | EO-F613FEE0E9                   |
| Generated       | 2026-07-31                      |

## Product Overview

MAGNET DX3 6/10 KA D 4P 32A  
CP Electronics 4 Pole 4 Core 8m 1.5mm<sup>2</sup> LSF Luminaire Lead Red Plug  
DX<sup>3</sup> 6000/10kA Circuit Breaker - 4P - 400V~ - 32A - D curve

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path      **LEGRAND > TERTIARY CIRCUIT BREAKERS**

## Additional Product Information

The free end has a 70mm strip for the inner cores with a 10mm ferrule  
ETIM for 408150 Circuit breakers and fuses (EC000042)  
Feature Name  
Feature Value  
Explosion-proof (EF004663)  
No  
Connectable conductor cross section solid-core (EF007337)  
1.5 mm<sup>2</sup>  
Ambient temperature during operating (EF007515)  
-25 °C  
Degree of protection (IP) (EF005474)  
IP20  
Concurrently switching neutral conductor (EF005997)  
Yes

Voltage type (EF000187)

AC

Rated short-circuit breaking capacity  $I_{cn}$  according to EN 60898 at 400 V (EF009555)

6 kA

Additional equipment possible (EF008148)

Yes

Rated short-circuit breaking capacity  $I_{cu}$  according to IEC 60947-2 at 400 V (EF009558)

10 kA

Rated short-circuit breaking capacity  $I_{cu}$  according to IEC 60947-2 at 230 V (EF009557)

25 kA

Rated impulse withstand voltage  $U_{imp}$  (EF011980)

4 kV

Number of protected poles (EF005548)

4

Frequency (EF000416)

50 Hz

Built-in depth (EF000218)

44 mm

Number of poles (total) (EF008618)

4

Pollution degree (EF002570)

2

Width in number of modular spacings (EF002950)

4

Rated insulation voltage  $U_i$  (EF001366)

500 V

Connectable conductor cross section multi-wired (EF007343)

1.5 mm<sup>2</sup>

Rated current (EF000227)

32 A

Flush-mounted installation (EF007517)

Yes

Release characteristic (EF000889)

D

Rated voltage (EF000228)

400 V

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 408150 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.