

## INDUSTRIAL COMPONENT DATA

## 409885 LEGRAND AUTOMATIC DX3 3P MA63 25KA

Brand: LEGRAND | Manufacturer Part Number: 409885



|                 |                                 |
|-----------------|---------------------------------|
| Manufacturer    | LEGRAND                         |
| MPN / Reference | 409885                          |
| Catalog number  | 409885                          |
| Category        | Miniature circuit breaker (MCB) |
| Minimum order   | 1 Pcs                           |
| Document ID     | EO-FD53D0DAF3                   |
| Generated       | 2026-07-29                      |

## Product Overview

AUTOMATIC DX3 3P MA63 25KA

Automatic DX3 MA 25kA - 3P - 400V~ - 63 A - only magnetic

Automatic DX<sup>3</sup> MA 25kA - 3P - 400V~ - 63A - magnetic only

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification &amp; Catalog Path

Catalog path LEGRAND &gt; INDUSTRIAL CIRCUIT BREAKERS

## Additional Product Information

## Product features

Three-pole 400 V~ - Only magnet - rated current: 63 - Number of modules: 4,5 General characteristics

MCB DX3 MA - 25 kA - breakers only magnetic protection of the outputs - breaking capacity: 25 kA - UNE-en 60947-2 - 400

V~ - Support the auxiliary and all of the controllers-motorized - Connection: top entry and bottom exit for terminals with

screws - Are associated to the blocks of differential adaptive

ETIM for 409885 Circuit breakers and fuses (EC000042)

Feature Name

Feature Value

Explosion-proof (EF004663)

No

Connectable conductor cross section solid-core (EF007337)

1.5 mm<sup>2</sup>

Ambient temperature during operating (EF007515)

-25 °C

Degree of protection (IP) (EF005474)

IP20

Concurrently switching neutral conductor (EF005997)

No

Voltage type (EF000187)

AC

Additional equipment possible (EF008148)

Yes

Rated short-circuit breaking capacity Icu according to IEC 60947-2 at 400 V (EF009558)

25 kA

Rated short-circuit breaking capacity Icu according to IEC 60947-2 at 230 V (EF009557)

50 kA

Rated impulse withstand voltage Uimp (EF011980)

6 kV

Number of protected poles (EF005548)

3

Frequency (EF000416)

50 Hz

Built-in depth (EF000218)

47 mm

Number of poles (total) (EF008618)

3

Pollution degree (EF002570)

3

Width in number of modular spacings (EF002950)

4.5

Rated insulation voltage Ui (EF001366)

500 V

Connectable conductor cross section multi-wired (EF007343)

1.5 mm<sup>2</sup>

Rated current (EF000227)

63 A

Flush-mounted installation (EF007517)

Yes

Release characteristic (EF000889)

M...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 409885 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.