

INDUSTRIAL COMPONENT DATA

410015 LEGRAND MAGNET DX3 36kA C 2P 80A

Brand: LEGRAND | Manufacturer Part Number: 410015



Manufacturer	LEGRAND
MPN / Reference	410015
Catalog number	410015
Category	Miniature circuit breaker (MCB)
Minimum order	1 Pcs
Document ID	EO-A759157255
Generated	2026-07-31

Product Overview

MAGNET DX3 36kA C 2P 80A

Circuit breaker DX3 36kA - 2P - 230/400V~ - 80 A - curve C

DX3 Circuit Breaker 36kA - 2P - 230/400V~ - 80A - C curve

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LEGRAND > INDUSTRIAL CIRCUIT BREAKERS

Additional Product Information

Product features

Bipolar 230/400 V~ - Curve C - nominal Intensity: 80 - Number of modules: 3 General characteristics

MCB DX3 - 36 kA - breakers circuit - curve C - protection of the outputs - breaking capacity: 36 kA - UNE-en 60947-2 - 400

V~ - Support the auxiliary and all of the controllers-motorized - Connection: top entry and bottom exit for terminals with screws - automatic 2P/3P, and 4P are associated to the blocks of differential adaptive

ETIM for 410015 Circuit breakers and fuses (EC000042)

Feature Name

Feature Value

Explosion-proof (EF004663)

No

Connectable conductor cross section solid-core (EF007337)

6 mm²

Ambient temperature during operating (EF007515)

-25 °C

Degree of protection (IP) (EF005474)

IP20

Concurrently switching neutral conductor (EF005997)

No

Voltage type (EF000187)

AC

Additional equipment possible (EF008148)

Yes

Rated short-circuit breaking capacity Icu according to IEC 60947-2 at 400 V (EF009558)

36 kA

Rated short-circuit breaking capacity Icu according to IEC 60947-2 at 230 V (EF009557)

72 kA

Rated impulse withstand voltage Uimp (EF011980)

6 kV

Number of protected poles (EF005548)

2

Frequency (EF000416)

50 Hz

Built-in depth (EF000218)

47 mm

Number of poles (total) (EF008618)

2

Pollution degree (EF002570)

3

Width in number of modular spacings (EF002950)

3

Rated insulation voltage Ui (EF001366)

500 V

Connectable conductor cross section multi-wired (EF007343)

6 mm²

Rated current (EF000227)

80 A

Flush-mounted installation (EF007517)

Yes

Release charact...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 410015 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.