INDUSTRIAL COMPONENT DATA

410151 LEGRAND MAGNET DX3 50kA C 2P 32A

Brand: LEGRAND | Manufacturer Part Number: 410151

Manufacturer	**LEGRAND**
MPN / Reference	**410151**
Catalog number	**410151**
Category	**Miniature circuit breaker (MCB)**
Minimum order	**1 Pcs**
Document ID	**EO-02936181D3**
Generated	**2026-08-02**

Product Overview

MAGNET DX3 50kA C 2P 32A
MCB - DX³ - 50 kA - 2P - 230/400 V~ - 32 A - C curve
DX³ 50kA Circuit Breaker - 2P - 230/400V~ - 32A - C curve

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	**LEGRAND > INDUSTRIAL CIRCUIT BREAKERS**

Additional Product Information

Pack (number of units)1
Volume (dm3)0.605
Weight (g)456.00
Product characteristics2-pole - 230/400 V~
C curve
Nominal rating In : 32 A
Number of modules : 3
General characteristicsMCBs DX³ - 50 kA - thermal magnetic MCBs from 10 A to 63 A - C and D curvesBreaking capacity: 50 kA - IEC 60947-2 - 400 V~
Can be equipped with DX³ auxiliaries and accessories
ETIM for 410151 Circuit breakers and fuses (EC000042)
Feature Name
Feature Value
Explosion-proof (EF004663)

No
Connectable conductor cross section solid-core (EF007337)
1.5 mm²
Ambient temperature during operating (EF007515)
-25 °C
Degree of protection (IP) (EF005474)
IP20
Concurrently switching neutral conductor (EF005997)
No
Voltage type (EF000187)
AC
Additional equipment possible (EF008148)
Yes
Rated short-circuit breaking capacity Icu according to IEC 60947-2 at 400 V (EF009558)
50 kA
Rated short-circuit breaking capacity Icu according to IEC 60947-2 at 230 V (EF009557)
100 kA
Rated impulse withstand voltage Uimp (EF011980)
6 kV
Number of protected poles (EF005548)
2
Frequency (EF000416)
50 Hz
Built-in depth (EF000218)
47 mm
Number of poles (total) (EF008618)
2
Pollution degree (EF002570)
3
Width in number of modular spacings (EF002950)
3
Rated insulation voltage Ui (EF001366)
500 V
Connectable conductor cross section multi-wired (EF007343)
1.5 mm²
Rated current (EF000227)
32 A
Flush-mounted installation (EF007517)
Yes
Release characteristic (EF000889)
C
Rated voltage (EF000228)
400 V

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 410151 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.