

## INDUSTRIAL COMPONENT DATA

## 411204 LEGRAND MAGNET DIFFER DX3 4P 300mA C10

Brand: LEGRAND | Manufacturer Part Number: 411204



|                 |                               |
|-----------------|-------------------------------|
| Manufacturer    | LEGRAND                       |
| MPN / Reference | 411204                        |
| Catalog number  | 411204                        |
| Category        | Earth leakage circuit breaker |
| Minimum order   | 1 Pcs                         |
| Document ID     | EO-605BE2CC52                 |
| Generated       | 2026-07-29                    |

## Product Overview

MAGNET DIFFER DX3 4P 300mA C10

DX<sup>3</sup> 6000A 4 Pole 10A AC Type RCBO C Curve 300mADifferential circuit breaker DX<sup>3</sup> 6000/10kA curve C - 4P - 10A-300mA - Type AC

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification &amp; Catalog Path

Catalog path      LEGRAND &gt; TERTIARY CIRCUIT BREAKERS

## Additional Product Information

Breaking capacity: 6000 - IEC 61009-1 - 10 kA / IEC 60947-2 for single pole + neutral, double and four pole \* AC type :  
detect AC component faults Enhanced immunity to unwanted tripping in disturbed environments Can be equipped with DX3  
auxiliaries and accessories Number of poles (total) 4  
Number of protected poles 4  
Rated voltage 400 V  
Rated current 10 A  
Rated fault current 0.3 A  
Leakage current type AC  
Current limiting class 3  
Rated short-circuit breaking capacity according to EN 61009 6 kA  
Rated short-circuit breaking capacity Icn according to EN 61009-1 6 kA  
Surge current capacity 0.25 kA  
Voltage type AC  
Frequency 50 Hz

Release characteristic C  
Concurrently switching neutral conductor Yes  
With interlocking device Yes  
Pollution degree 2  
Width in number of modular spacings 4  
Built-in depth 44 mm  
Anti- nuisance tripping version No  
Degree of protection (IP) IP20  
ETIM for 411204 Circuit breakers and fuses (EC000905)  
Feature Name  
Feature Value  
Frequency (EF005455)  
50 Hz  
Degree of protection (IP) (EF005474)  
IP20  
Leakage current type (EF002560)  
AC  
Voltage type (EF000187)  
AC  
Concurrently switching neutral conductor (EF005997)  
Yes  
Surge current capacity (EF002564)  
0.25 kA  
Anti- nuisance tripping version (EF009497)  
No  
Rated short-circuit breaking capacity according to IEC 60947-2 (EF006065)  
10 kA  
Rated short-circuit breaking capacity according to EN 61009 (EF012628)  
6 kA  
Rated short-circuit breaking capacity Icn according to EN 61009-1 (EF011981)  
6 kA  
Rated fault current (EF002358)  
0....

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 411204 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.