

INDUSTRIAL COMPONENT DATA

411500 LEGRAND DIFFERENTIAL DX3 2/16/10 AC

Brand: LEGRAND | Manufacturer Part Number: 411500



Manufacturer	LEGRAND
MPN / Reference	411500
Catalog number	411500
Category	Residual current circuit breaker (RCCB)
Minimum order	1 Pcs
Document ID	EO-719D130B5E
Generated	2026-07-29

Product Overview

DIFFERENTIAL DX3 2/16/10 AC
DX3-ID 2 Pole 16A AC Type RCD 10mA
DX3 Differential Switch - 2P - 230V~ - 16A - AC Type - 10mA - 2mod

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	LEGRAND > TERTIARY CIRCUIT BREAKERS
--------------	-------------------------------------

Additional Product Information

Conform to IEC 61008-1 * AC type : detect AC component faults * A type : detect AC and DC component faults Enhanced immunity to unwanted tripping in disturbed environments Can be equipped with DX3 auxiliaries and accessories Number of poles 2
Rated voltage 230 V
Rated current 16 A
Rated fault current 0.01 A
Rated insulation voltage U_i 250 V
Rated impulse withstand voltage U_{imp} 4 kV
Mounting method DIN rail
Leakage current type AC
Selective protection No
Short-time delayed tripping No
Short-circuit breaking capacity (I_{cw}) 10 kA
Surge current capacity 0.25 kA

Voltage type AC
With interlocking device Yes
Frequency 50 Hz
Additional equipment possible Yes
Degree of protection (IP) IP20
Width in number of modular spacings 2
Built-in depth 44 mm
Ambient temperature during operating -25-60 °C
Pollution degree 2
Connectable conductor cross section multi-wired 0.75-35 mm²
Connectable conductor cross section solid-core 0.75-50 mm²
Colour Grey
RAL-number (similar) 7035
Explosion-proof No
Width 35.6 mm
Height 94.8 mm
Depth 77.8 mm
degree of impact strength (IK) IK04
Storage temperature -40-70 °C
Electric supplying direction By the top or bottom
Terminal marking indication No
Stress test conformity (1000V) Yes
Halogen free Yes
Connection type Screwed terminal , Busbar and cable
Label space/information surface Yes
ETIM for 411500 Circuit breakers and fuses (EC000003)
Feature Name
Feature Value
Explosion-proof (EF004663)
No
Connectable conductor cross section solid-core (EF007337)
0.75 mm²
F...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 411500 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.