

INDUSTRIAL COMPONENT DATA

411668 LEGRAND DIFFERENTIAL DX3 4/40/300 AC-S

Brand: LEGRAND | Manufacturer Part Number: 411668



Manufacturer	LEGRAND
MPN / Reference	411668
Catalog number	411668
Category	Residual current circuit breaker (RCCB)
Minimum order	1 Pcs
Document ID	EO-3858FA601C
Generated	2026-07-31

Product Overview

DIFFERENTIAL DX3 4/40/300 AC-S

Inter. differential DX3 -4P - 400V~40A -AC -300mA select.- 4 mód.

Differential switch DX³ - 4P - 400V~ - 40A - Type AC - 300mA select. - 4mod

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LEGRAND > TERTIARY CIRCUIT BREAKERS

Additional Product Information

Product features

Tetrapolares 400 V~ Type AC - Sensitivity: 300 selective mA - In: 40 - Number of modules: 4 General characteristics
Circuit breakers DX3-ID - top entry/bottom exit - Comply with standard UNE en 61008-1 - Type AC: detect the defects of component ac - Type To: detect defects in components alternating current and direct current (specialized circuits: cookers, cooking plates, washing machines, etc) - Type Hpi: detect defects in components, alternating and continuous (type A) with immunity with regard to the false alarms. (environments with disturbances: circuits, computer, impact of lightning, fluorescent lamps, etc) - Type B: detect the defects of components, alternating and continuous, and the defects of direct current without ripple (machinery with varying speed, pv systems, call centers, medical supplies, etc) - Suitable for auxiliary controls motor and connection modules DX3 (except Type B) - Connection screw/screw: top entry and bottom exit for terminals with screws

ETIM for 411668 Circuit breakers and fuses (EC000003)

Feature Name

Feature Value

Explosion-proof (EF004663)

No
Connectable conductor cross section solid-core (EF007337)
0.75 mm²
Frequency (EF005455)
50 Hz
Selective protection (EF002561)
Yes
Short-circuit breaking capacity (I_{cn}) (EF002562)
10 kA
Ambient temperature during operating (EF007515)
-25 °C
Degree of protection (IP) (EF005474)
IP20
Leakage current type (EF002560)
AC
Voltage type (EF000187)
AC
Additional equipment possible (EF008148)
Yes...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 411668 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.