

## INDUSTRIAL COMPONENT DATA

## 411695 LEGRAND DIFFERENTIAL DX3 4/40/30 HPI

Brand: LEGRAND | Manufacturer Part Number: 411695



|                 |                                         |
|-----------------|-----------------------------------------|
| Manufacturer    | LEGRAND                                 |
| MPN / Reference | 411695                                  |
| Catalog number  | 411695                                  |
| Category        | Residual current circuit breaker (RCCB) |
| Minimum order   | 1 Pcs                                   |
| Document ID     | EO-1C183C8068                           |
| Generated       | 2026-07-27                              |

## Product Overview

DIFFERENTIAL DX3 4/40/30 HPI

Inter. differential DX3 - 4P - 400V~ - 40A - type-Hpi - 30mA - 4 mód.

DX3 Differential Switch - 4P - 400V~ - 40A - Hpi Type - 30mA - 4mod

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification &amp; Catalog Path

Catalog path LEGRAND &gt; TERTIARY CIRCUIT BREAKERS

## Additional Product Information

## Product features

Tetrapolares 400 V~ Type Hpi - Sensitivity: 30 mA - In: 40 - Number of modules: 4 General characteristics

Circuit breakers DX3-ID - top entry/bottom exit - Comply with standard UNE en 61008-1 - Type AC: detect the defects of component ac - Type To: detect defects in components alternating current and direct current (specialized circuits: cookers, cooking plates, washing machines, etc) - Type Hpi: detect defects in components, alternating and continuous (type A) with immunity with regard to the false alarms. (environments with disturbances: circuits, computer, impact of lightning, fluorescent lamps, etc) - Type B: detect the defects of components, alternating and continuous, and the defects of direct current without ripple (machinery with varying speed, pv systems, call centers, medical supplies, etc) - Suitable for auxiliary controls motor and connection modules DX3 (except Type B) - Connection screw/screw: top entry and bottom exit for terminals with screws

ETIM for 411695 Circuit breakers and fuses (EC000003)

Feature Name

Feature Value

Explosion-proof (EF004663)

No  
Connectable conductor cross section solid-core (EF007337)  
0.75 mm<sup>2</sup>  
Frequency (EF005455)  
50 Hz  
Selective protection (EF002561)  
No  
Short-circuit breaking capacity (I<sub>cn</sub>) (EF002562)  
10 kA  
Ambient temperature during operating (EF007515)  
-25 °C  
Degree of protection (IP) (EF005474)  
IP20  
Leakage current type (EF002560)  
F  
Voltage type (EF000187)  
AC  
Additional equipment possible (EF008148)  
Yes  
Mounting me...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 411695 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.