

INDUSTRIAL COMPONENT DATA**411966 LEGRAND DX3 4/40/30 B DIFFERENTIAL**

Brand: LEGRAND | Manufacturer Part Number: 411966



Manufacturer	LEGRAND
MPN / Reference	411966
Catalog number	411966
Category	Residual current circuit breaker (RCCB)
Minimum order	1 Pcs
Document ID	EO-C33F53A51A
Generated	2026-08-01

Product Overview**DX3 4/40/30 B DIFFERENTIAL**Differential switch DX³ - 4P- 400V~ - 40A - type B - 30mA - 4 mód.DX³ Differential Switch - 4P - 400V~ - 40A - Type B - 30mA - 4mod**STRUCTURED PRODUCT DATA****Technical Specifications**

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog PathCatalog path **LEGRAND > TERTIARY CIRCUIT BREAKERS****Additional Product Information****Product features**

Protects people against indirect contacts.

It provides protection against fire hazards due to a persistent ground fault current.

It can also be used to control and isolate the installation. General features

DX³-ID differential switches - upper input/bottom output - Comply with UNE EN 61008-1 standard - Type AC: detect alternating component defects - Type A: detect defects of alternating and continuous components (specialized circuits: kitchens, hobs, washing machines, etc.) - Hpi type: detect defects of alternating and continuous components (type A) with reinforced immunity to untimely triggering (environments with disturbances: computer circuits, lightning strikes, fluorescent lamps, etc.) - Type B: detect defects of alternating and continuous components and defects of direct current without ripple (machinery with speed variation, photovoltaic installations, call centers, medical equipment, etc.) - Suitable for auxiliaries, motorized controls and DX³ connection modules (except Type B) - Screw/screw connection: upper and lower output by terminals with screws

ETIM for 411966 Circuit breakers and fuses (EC000003)

Feature Name

Feature Value

Explosion-proof (EF004663)

No

Connectable conductor cross section solid-core (EF007337)

0.75 mm²

Frequency (EF005455)

50 Hz

Selective protection (EF002561)

No

Short-circuit breaking capacity (I_{cn}) (EF002562)

10 kA

Ambient temperature during operating (EF007515)

-25 °C

Degree of protection (IP) (EF005474)

IP20

Leakage current...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEWSend LEGRAND / 411966 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.