

INDUSTRIAL COMPONENT DATA

412170 LEGRAND CONNECTED TELESWITCH

Brand: LEGRAND | Manufacturer Part Number: 412170



Manufacturer	LEGRAND
MPN / Reference	412170
Catalog number	412170
Category	Latching relay
Minimum order	1 Pcs
Document ID	EO-EDDBBE59E0
Generated	2026-07-29

Product Overview

CONNECTED TELESWITCH

CX³ with Netatmo Single Pole 16A 230V AC Connected Latching Relay

Connected switch for electrical panel

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	LEGRAND
--------------	---------

Additional Product Information

Function Electronic switch

Mounting method DIN rail

Width in number of modular spacings 1

Built-in depth 44 mm

Number of contacts as normally open contact 1

Rated switch current 16 A

Supply voltage 240-240 V

Voltage type (supply voltage) AC

Max. incandescent lamp load 3840 W

Max. load fluorescent lamp 3000 VA

Max. switching current (cos phi = 0.6) 16 A

Suitable for manual operation Yes

Width 17.8 mm

Height 95.9 mm

Depth 70.1 mm
degree of impact strength (IK) IK04
Degree of protection (IP) IP3X
Operating / setting temperature -5-45 °C
Storage temperature -40-70 °C
Electric supplying direction Not applicable
Terminal marking indication Yes
Stress test conformity (1000V) Yes
Halogen free Yes
Connection type Screwed terminal , Cable
Terminals capacity 0.75-6 mm²
Label space/information surface Yes
ETIM for 412170 Modular devices for distribution board/surface mounting (EC000188)
Feature Name
Feature Value
Max. load fluorescent lamp (EF004971)
3000 VA
Function (EF000030)
Electronic switch
Voltage type (supply voltage) (EF002991)
AC
Max. switching current (cos phi = 0.6) (EF004920)
16 A
Width in number of modular spacings (EF002950)
1
Max. incandescent lamp load (EF004952)
3840 W
Supply voltage (EF004127)
240 V
Mounting method (EF000003)
DIN rail
Number of contacts as normally open contact (EF008256)
1
Rated switch current (EF006706)
16 A
Built-in depth (EF000218)
44 mm
Suitable for manual operation (EF002978)
Yes

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 412170 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.