

## INDUSTRIAL COMPONENT DATA

## 412171 LEGRAND Smart Contactor

Brand: LEGRAND | Manufacturer Part Number: 412171



|                 |                                               |
|-----------------|-----------------------------------------------|
| Manufacturer    | LEGRAND                                       |
| MPN / Reference | 412171                                        |
| Catalog number  | 412171                                        |
| Category        | Installation contactor for distribution board |
| Minimum order   | 1 Pcs                                         |
| Document ID     | EO-03FE016A8C                                 |
| Generated       | 2026-07-29                                    |

## Product Overview

Smart Contactor  
CX<sup>3</sup> with Netatmo 20A 230V AC Connected Contactor  
Connected contactor for electrical panel

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification &amp; Catalog Path

|              |         |
|--------------|---------|
| Catalog path | LEGRAND |
|--------------|---------|

## Additional Product Information

Rated operating voltage 240-240 V  
Rated operation current 20 A  
Voltage type (operating voltage) AC  
Number of contacts as normally open contact 1  
Slider for hand switch No  
Width in number of modular spacings 1  
Additional equipment possible No  
Degree of protection (IP) IP3X  
Width 17.8 mm  
Height 95.9 mm  
Depth 70.1 mm  
degree of impact strength (IK) IK04  
Operating / setting temperature -5-45 °C  
Storage temperature -40-70 °C

Frequency 50-50 Hz  
Terminal marking indication Yes  
Colour Grey  
RAL-number 7035  
Halogen free Yes  
Terminals capacity 0.75-6 mm<sup>2</sup>  
Connection type Cable  
Label space/information surface Yes  
Mounting method DIN rail  
ETIM for 412171 Modular devices for distribution board/surface mounting (EC001653)  
Feature Name  
Feature Value  
Rated operation current (EF007679)  
20 A  
Degree of protection (IP) (EF005474)  
IP3X  
Width in number of modular spacings (EF002950)  
1  
Additional equipment possible (EF008148)  
No  
Number of contacts as normally open contact (EF008256)  
1  
Slider for hand switch (EF005240)  
No  
Voltage type (operating voltage) (EF005294)  
AC  
Rated operating voltage (EF001435)  
240 V

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 412171 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.