


INDUSTRIAL COMPONENT DATA

412215 LEGRAND LIM SOB+INT T2 40KA 3P+NG +SD

Brand: LEGRAND | Manufacturer Part Number: 412215



Manufacturer	LEGRAND
MPN / Reference	412215
Catalog number	412215
Category	Surge protection device for power supply systems
Minimum order	1 Pcs
Document ID	EO-3B82D83A8C
Generated	2026-08-04

Product Overview

LIM SOB+INT T2 40KA 3P+NG +SD

SPD with ICC protection 25KA T2 IMAX 40KA 3P+N with left fault signaling

SPD with ICC Protection 25KA T2 IMAX 40KA 3P+N

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LEGRAND > MOTOR CIRCUIT BREAKERS

Additional Product Information

Product features

General features

ETIM for 412215 Earthing, lightning and surge protection (EC000941)

Feature Name

Feature Value

System configuration TN-C-S (EF009933)

Yes

Degree of protection (IP) (EF005474)

IP20

Nominal voltage AC (EF004220)

400 V

System configuration TN-S (EF009930)

Yes

Construction size (EF002566)

8 modular spacing
System configuration other (EF009932)
No
Mounting method (EF000003)
DIN rail (top hat rail) 35 mm
System configuration TT (EF009931)
Yes
Signalling at the device (EF004241)
Optic
Max. discharge surge current (8/20) (EF012274)
20 kA
Number of conductors (without earthing) (EF001148)
4
Voltage protection level (EF003525)
2.5 kV
System configuration IT (EF009927)
No
System configuration DC (EF009926)
No
System configuration TN-C (EF009929)
Yes
System configuration TN (EF009928)
Yes
Max. continuous voltage AC (EF004198)
320 V
Voltage protection level N-PE (EF008796)
1.5 kV
Integrated backup fuse (EF008797)
Yes
Voltage protection level L-N (EF004236)
2.5 kV
Nominal discharge surge current (8/20) (EF004214)
20 kA
Category type 2 (EF004230)
Yes
With remote signalling contact (EF000422)
Yes
Max. conductor cross section solid (solid, stranded) (EF008827)
35 mm²
Max. conductor cross section flexible (fine-strand) (EF008828)
25 mm²

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 412215 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.