

INDUSTRIAL COMPONENT DATA

412282 LEGRAND LIMIT SOBRET T1 25KA 3P +SD

Brand: LEGRAND | Manufacturer Part Number: 412282



Manufacturer	LEGRAND
MPN / Reference	412282
Catalog number	412282
Category	Surge protection device for power supply systems
Minimum order	1 Pcs
Document ID	EO-E65FAA5B4B
Generated	2026-08-02

Product Overview

LIMIT SOBRET T1 25KA 3P +SD

SPD - high risk level installation - T1+T2 - limp 25 kA/pole - 3P

Surge limiter T1 - very high risk inst. - limp 25kA/pole - 3P

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **LEGRAND > MOTOR CIRCUIT BREAKERS**

Additional Product Information

Pack (number of units)1

Volume (dm3)2.363

Weight (g)1 227.00

Product characteristicsSPDs for high risk level installations

SPDs for big installations with external lightning protection (LPS) and for high risk level installations according to EN/IEC 62305 standards

SPDs with plug-in modules and status indicators:Green: SPD operational

Red: plug-in modules to be replaced

T1 + T2 - limp 25 kA/pole

Up: 1.5 kV - Uc: 350 V~

Earthing systems: TT, TNC, TNS.

Recommended MCCB: DPX³ 160 - 80 A

Number of poles : 3P

I_{total} (10/350) : 75 kA

Remote status monitoring (FS contact) : Yes

Number of modules : 6

General characteristics Class I + II (T1+T2) low voltage SPDs Protection against transient overvoltage for 230/400 V~ power networks (50/60 Hz).

SPDs compliant with EN/IEC 61643-11 standards

Recommended for main distribution boards

Class I+II (T1+T2) : SPDs tested and specified according to both T1 and T2 test classes

ETIM for 412282 Earthing, lightning and surge protection (EC000941)

Feature Name

Feature Value

System configuration TN-C-S (EF009933)

Yes

Degree of protection (IP) (EF005474)

IP20

Nominal voltage AC (EF004220)

400 V

System configuration TN-S (EF009930)

No

Construction size (EF002566)

6 modular spacing

System configuration other (EF009932)

No

Mounting method (EF000003)

DIN rail (top hat rail) 35 mm

System configuration TT (EF009931)

No

Signalling at the device (EF004241)

Optic

Number of conductors (without earthing) (EF001148)

3

Voltage protection level (EF003525)

1.5 kV

Sys...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 412282 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.