

## INDUSTRIAL COMPONENT DATA

## 416126 LEGRAND CTX 3P 32A 2NO2NC 230V AC

Brand: LEGRAND | Manufacturer Part Number: 416126



|                 |                               |
|-----------------|-------------------------------|
| Manufacturer    | LEGRAND                       |
| MPN / Reference | 416126                        |
| Catalog number  | 416126                        |
| Category        | Power contactor, AC switching |
| Minimum order   | 1 Pcs                         |
| Document ID     | EO-4176F22E1E                 |
| Generated       | 2026-07-29                    |

## Product Overview

CTX 3P 32A 2NO2NC 230V AC

3-pole contactors CTX<sup>3</sup> 40 - 32 A 230 V~ - 2 NO + 2 NC - screw terminalsCTX<sup>3</sup> 40 - 32A - 230V~ - 2 NA + 2 NC Three-Pole Contactors - Terminal Blocks w/Screw

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification &amp; Catalog Path

Catalog path LEGRAND &gt; INDUSTRIAL CONTACTORS / SWITCHES

## Additional Product Information

Pack (number of units)1

Volume (dm<sup>3</sup>)0.668

Weight (g)568.00

Product characteristicsCTX<sup>3</sup> 40

With integrated auxiliary contacts

Power terminals: screw terminals

32 A (AC3) - 50 A (AC1)

Screw terminals

3-phase motor 400/415 V : 15 kW

Control Voltage : 230 V~

Integrated auxiliary contacts : 2 NO + 2 NC

General characteristics3-pole contactors CTX<sup>3</sup> - 9 A to 100 A industrial contactorsConform to IEC 60947-1, IEC 60947-4-1Can be equipped with RTX<sup>3</sup> thermal relays add-on auxiliary contact blocks, time delay blocks, capacitor switching units and CTX<sup>3</sup> interlocking

ETIM for 416126 Low-voltage industrial controls and switchgear (EC000066)

Feature Name

Feature Value

Rated operation current  $I_e$  at AC-1, 400 V (EF001393)

50 A

Number of normally open contacts as main contact (EF001374)

3

Number of auxiliary contacts as normally open contact (EF001376)

2

Number of normally closed contacts as main contact (EF001375)

0

Rated operation power at AC-3, 400 V (EF001364)

15 kW

Number of auxiliary contacts as normally closed contact (EF001377)

2

Rated operation current  $I_e$  at AC-4, 400 V (EF008495)

17 A

Voltage type for actuating (EF008242)

AC

Rated operation power at AC-4, 400 V (EF008496)

7.5 kW

Rated operation current  $I_e$  at AC-3, 400 V (EF001392)

32 A

Modular version (EF001126)

Yes

Rated control supply voltage AC 50 Hz (EF003978)

195.5 V

Type of electrical connection of main circuit (EF006819)

Cable clamp

Rated control supply voltage AC 60 Hz (EF003979)

195.5 V

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 416126 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.