

INDUSTRIAL COMPONENT DATA

416259 LEGRAND CTX 3P 130A 2NO2NC 400V-440V

Brand: LEGRAND | Manufacturer Part Number: 416259



Manufacturer	LEGRAND
MPN / Reference	416259
Catalog number	416259
Category	Power contactor, AC switching
Minimum order	1 Pcs
Document ID	EO-69E2119D3B
Generated	2026-08-03

Product Overview

CTX 3P 130A 2NO2NC 400V-440V

3-pole contactors CTX³ 150 - 130 A - 400-440 V~ - 2 NO + 2 NC - lug terminalsContactor CTX³ 3P 130A 2NO2NC 380V - 440V AC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LEGRAND > INDUSTRIAL CONTACTORS / SWITCHES

Additional Product Information

Pack (number of units)1

Volume (dm³)2.991

Weight (g)2 403.00

Product characteristicsCTX³ 150

With integrated auxiliary contacts

130 A (AC3) - 160 A (AC1)

Cage terminals

3-phase motor 400/415 V : 60 kW

Control Voltage : 400-440 V~

Integrated auxiliary contacts : 2 NO + 2 NC

General characteristics3-pole contactors CTX³ - 130 A to 800 A industrial contactorsConform to IEC 60947-1, IEC 60947-4-1Can be equipped with RTX³ thermal relays add-on auxiliary contact blocks, time delay blocks (except CTX³ 225/400/800) and CTX³ interlocking

ETIM for 416259 Low-voltage industrial controls and switchgear (EC000066)

Feature Name

Feature Value

Rated operation current I_e at AC-1, 400 V (EF001393)

160 A

Number of normally open contacts as main contact (EF001374)

3

Number of auxiliary contacts as normally open contact (EF001376)

2

Number of normally closed contacts as main contact (EF001375)

0

Rated operation power at AC-3, 400 V (EF001364)

60 kW

Number of auxiliary contacts as normally closed contact (EF001377)

2

Rated operation current I_e at AC-4, 400 V (EF008495)

90 A

Voltage type for actuating (EF008242)

AC

Rated operation power at AC-4, 400 V (EF008496)

45 kW

Rated operation current I_e at AC-3, 400 V (EF001392)

130 A

Modular version (EF001126)

Yes

Rated control supply voltage AC 50 Hz (EF003978)

340 V

Type of electrical connection of main circuit (EF006819)

Screw connection

Rated control supply voltage AC 60 Hz (EF003979)

340 V

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 416259 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.