

## INDUSTRIAL COMPONENT DATA

## 419929 LEGRAND MAGNET. HOUSING RX3 1P+N 32A

Brand: LEGRAND | Manufacturer Part Number: 419929



|                 |                                 |
|-----------------|---------------------------------|
| Manufacturer    | LEGRAND                         |
| MPN / Reference | 419929                          |
| Catalog number  | 419929                          |
| Category        | Miniature circuit breaker (MCB) |
| Minimum order   | 6 Pcs                           |
| Document ID     | EO-43ACF6C8E0                   |
| Generated       | 2026-08-01                      |

## Product Overview

MAGNET. HOUSING RX3 1P+N 32A

Circuit breaker RX3 - 1P+N - 230 V~ - 32 A - curve C

RX3 Circuit Breaker - 1P+N - 230V~ - 32A - C curve

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification &amp; Catalog Path

Catalog path LEGRAND &gt; HOME CIRCUIT BREAKERS

## Additional Product Information

## Product features

Circuit breaker circuit breaker RX3 single-Pole + neutral 230 V~ - Curve C - rated current: 32 - Number of modules: 2

## General characteristics

Circuit RX3 - breakers from 10 a To 40 A - curve C - breaking capacity 6000A - According to UNE en-60898-1 - Screws, safety pins and headache, mixed - Use domestic - Mounting on profile symmetric - Capacity of embornamiento: 25 mm2 flexible/35 mm2 rigid

ETIM for 419929 Circuit breakers and fuses (EC000042)

Feature Name

Feature Value

Explosion-proof (EF004663)

No

Degree of protection (IP) (EF005474)

IP20

Rated short-circuit breaking capacity Icn according to EN 60898 at 230 V (EF009556)

6 kA  
Concurrently switching neutral conductor (EF005997)  
Yes  
Voltage type (EF000187)  
AC  
Additional equipment possible (EF008148)  
No  
Rated impulse withstand voltage Uimp (EF011980)  
4 kV  
Number of protected poles (EF005548)  
1  
Frequency (EF000416)  
50 Hz  
Built-in depth (EF000218)  
44 mm  
Number of poles (total) (EF008618)  
2  
Pollution degree (EF002570)  
2  
Width in number of modular spacings (EF002950)  
2  
Rated insulation voltage Ui (EF001366)  
400 V  
Rated current (EF000227)  
32 A  
Current limiting class (EF002568)  
3  
Flush-mounted installation (EF007517)  
Yes  
Release characteristic (EF000889)  
C  
Rated voltage (EF000228)  
230 V

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 419929 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.