

INDUSTRIAL COMPONENT DATA

419935 LEGRAND MAGNET. HOUSING RX3 2P 16A

Brand: LEGRAND | Manufacturer Part Number: 419935



Manufacturer	LEGRAND
MPN / Reference	419935
Catalog number	419935
Category	Miniature circuit breaker (MCB)
Minimum order	6 Pcs
Document ID	EO-11590CD496
Generated	2026-08-02

Product Overview

MAGNET. HOUSING RX3 2P 16A

Circuit breaker RX3 - 2P - 230/400 V~ - 16 A - curve C

RX³ Circuit Breaker - 2P - 230/400V~ - 16A - C curve

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LEGRAND > HOME CIRCUIT BREAKERS

Additional Product Information

Product features

Circuit breaker circuit breaker RX3 Bipolar 230/400 V~ - Curve C - rated current: 16 A - Number of modules: 2 General characteristics

Circuit RX3 - breakers from 10 a To 40 A - curve C - breaking capacity 6000A - According to UNE en-60898-1 - Screws, safety pins and headache, mixed - Use domestic - Mounting on profile symmetric - Capacity of embornamiento: 25 mm2 flexible/35 mm2 rigid

ETIM for 419935 Circuit breakers and fuses (EC000042)

Feature Name

Feature Value

Explosion-proof (EF004663)

No

Degree of protection (IP) (EF005474)

IP20

Concurrently switching neutral conductor (EF005997)

Yes

Voltage type (EF000187)

AC

Rated short-circuit breaking capacity I_{cn} according to EN 60898 at 400 V (EF009555)

6 kA

Additional equipment possible (EF008148)

No

Rated impulse withstand voltage U_{imp} (EF011980)

4 kV

Number of protected poles (EF005548)

1

Frequency (EF000416)

50 Hz

Built-in depth (EF000218)

44 mm

Number of poles (total) (EF008618)

2

Pollution degree (EF002570)

2

Width in number of modular spacings (EF002950)

2

Rated insulation voltage U_i (EF001366)

400 V

Rated current (EF000227)

16 A

Current limiting class (EF002568)

3

Flush-mounted installation (EF007517)

Yes

Release characteristic (EF000889)

C

Rated voltage (EF000228)

400 V

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 419935 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.