

INDUSTRIAL COMPONENT DATA

420248 LEGRAND DPX3250 mag. 4P 200A 36kA

Brand: LEGRAND | Manufacturer Part Number: 420248



Manufacturer	LEGRAND
MPN / Reference	420248
Catalog number	420248
Category	Power circuit-breaker for trafo/generator/installation protection
Minimum order	1 Pcs
Document ID	EO-2F173EBDEF
Generated	2026-08-03

Product Overview

DPX3250 mag. 4P 200A 36kA
MCCB thermal magnetic - DPX³ 250 - Icu 36 kA 400 V~ - 4P - 200 A
Automatic MCCB DPX³ 250 - circuit breaker - 4P - 36kA - 200A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **LEGRAND > DPX3 MOLDED BOX**

Additional Product Information

Pack (number of units)1
Volume (dm3)3.813
Weight (g)2 287.00
Product characteristicsMCCBs - fixed version
Thermal adjustable from 0,8 to 1 In
Magnetic adjustable from 5 to 10 In
Breaking capacity Icu 36 kA (400 V~)
4P
In : 200 A
General characteristicsDPX³ 250 thermal magnetic - MCCBs from 100 to 250 ACan be mounted on rail or on plate in XL³ cabinets and enclosures
MCCBs for switching, control isolation and protection of low voltage electrical lines
Supplied with fixing screws, connection plates for bars and cable lugs and insulated shields (phase barriers)
Can be fitted with cage terminals 120 mm² max. (flexible cable) or 150 mm² max. rigid cable and with DPX³ 160 and 250

common auxiliaries and accessories

Conform to IEC 60947-2

ETIM for 420248 Low-voltage industrial controls and switchgear (EC000228)

Feature Name

Feature Value

Degree of protection (IP) (EF005474)

IP30

Number of auxiliary contacts as change-over contact (EF003531)

1

Number of auxiliary contacts as normally closed contact (EF001377)

1

Adjustment range undelayed short-circuit release (EF007131)

1000 A

Integrated earth fault protection (EF007296)

No

With integrated under voltage release (EF001390)

Yes

Suitable for DIN rail (top hat rail) mounting (EF007250)

Yes

Device construction (EF008240)

Built-in device fixed built-in technique

Number of poles (EF001391)

4

Type of electrical connection of main circuit (EF006819)

Screw connection

Overload release current setting (EF002336)

160 A

Motor drive integrated (EF0...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 420248 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.