

INDUSTRIAL COMPONENT DATA

420300 LEGRAND DPX3250 INTER. 4P 250A

Brand: LEGRAND | Manufacturer Part Number: 420300



Manufacturer	LEGRAND
MPN / Reference	420300
Catalog number	420300
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-63B523EC49
Generated	2026-08-01

Product Overview

DPX3250 INTER. 4P 250A

DPX³-I 250 4 Pole 250A Trip-Free SwitchDPX³ -I 250 Free Disconnect Switch - 4P - 250A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LEGRAND > DPX3 MOLDED BOX

Additional Product Information

Version as main switch Yes

Version as maintenance-/service switch Yes

Version as safety switch Yes

Version as emergency stop installation Yes

Version as reversing switch No

Max. rated operation voltage Ue AC 690 V

Rated operating voltage 220-690 V

Rated permanent current Iu 250 A

Rated permanent current at AC-21, 400 V 250 A

Rated short-time withstand current Icw 1.7 kA

Rated operation power at AC-23, 400 V 100 kW

Conditioned rated short-circuit current Iq 1.7 kA

Number of poles 4

Number of auxiliary contacts as normally closed contact 1

Number of auxiliary contacts as normally open contact 1
Number of auxiliary contacts as change-over contact 1
Motor drive optional Yes
Motor drive integrated No
Voltage release optional Yes
Device construction Built-in device fixed built-in technique
Suitable for floor mounting Yes
Suitable for front mounting 4-hole No
Suitable for front mounting centre No
Suitable for distribution board installation Yes
Suitable for intermediate mounting No
Colour control element Grey
Type of control element Wing knob
Interlockable Yes
Type of electrical connection of main circuit Screw connection
Degree of protection (IP), front side IP30
ETIM for 420300 Low-voltage industrial controls and switchgear (EC000216)
Feature Name
Feature Value
Version as safety switch (EF006985)
Yes
Version as maintenance-/service switch (EF006986)
Yes
Number of auxiliary contacts as normally open contact (EF001376)
1
Max. rated operation voltage Ue AC (EF007355)
690 V
Version a...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 420300 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.