

**INDUSTRIAL COMPONENT DATA**

# 420756 LEGRAND DPX3250 mag. 3P+N/2 250A 70kA

Brand: LEGRAND | Manufacturer Part Number: 420756



|                 |                                                                   |
|-----------------|-------------------------------------------------------------------|
| Manufacturer    | LEGRAND                                                           |
| MPN / Reference | 420756                                                            |
| Catalog number  | 420756                                                            |
| Category        | Power circuit-breaker for trafo/generator/installation protection |
| Minimum order   | 1 Pcs                                                             |
| Document ID     | EO-5FBC113307                                                     |
| Generated       | 2026-08-03                                                        |

## Product Overview

DPX3250 mag. 3P+N/2 250A 70kA

Automatic MCCB DPX3 250 - magnetotérm - 3P+N/2 - Icu 70 kA (400 V~) - In 250 To

Automatic MCCB DPX<sup>3</sup> 250 - circuit breaker - 3P+N/2 - 70kA - 250A**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path **LEGRAND > DPX3 MOLDED BOX**

## Additional Product Information

**Product features**

Automatic moulded case circuit breaker - fixed version Thermal adjustable from 0,8 to 1 In Magnetic adjustable from 5 to 10

In breaking capacity Icu 70 kA (400 V~) - Number of poles: 3P+N/2 - In: 250 To General characteristics

DPX3 250 automatic power current protection 100-to 250 - Is mounted on a profile symmetrical or on mounting plate in

boxes and cabinets XL3 - Guarantee to the court, the control, the switching and protection of power lines, low voltage -

Includes separation plates, terminals cage connection 120 mm<sup>2</sup> maximum flexible cable and up to 150 mm<sup>2</sup> with

accessories - equipped with the auxiliary Settings - sealable - Meet the standard UNE-en 60947-2

ETIM for 420756 Low-voltage industrial controls and switchgear (EC000228)

Feature Name

Feature Value

Degree of protection (IP) (EF005474)

IP30

Number of auxiliary contacts as change-over contact (EF003531)

1

Number of auxiliary contacts as normally closed contact (EF001377)

1

Adjustment range undelayed short-circuit release (EF007131)

1250 A

Integrated earth fault protection (EF007296)

No

With integrated under voltage release (EF001390)

Yes

Suitable for DIN rail (top hat rail) mounting (EF007250)

Yes

Device construction (EF008240)

Built-in device fixed built-in technique

Number of poles (EF001391)

4

Type of electrical connection of main circuit (EF006819)

Screw connection

Overload release current setting (EF002336)

200 A

Motor drive integrated (EF006697)

No

Adjustment range short-term delayed short-ci...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 420756 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.