

INDUSTRIAL COMPONENT DATA

422011 LEGRAND DPX3 630 MT 3P+N/2 400A 36kA

Brand: LEGRAND | Manufacturer Part Number: 422011



Manufacturer	LEGRAND
MPN / Reference	422011
Catalog number	422011
Category	Power circuit-breaker for trafo/generator/installation protection
Minimum order	1 Pcs
Document ID	EO-77E10669EA
Generated	2026-07-29

Product Overview

DPX3 630 MT 3P+N/2 400A 36kA

DPX³ 630 3 Pole + N/2 400A Thermal Magnetic MCCB 36kAAutomatic MCCB DPX³ 630 - circuit breaker - 3P+N/2 - 36kA - 400A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LEGRAND > DPX3 MOLDED BOX

Additional Product Information

Rated permanent current I_n 400 A

Rated voltage 220-690 V

Rated short-circuit breaking capacity I_{cu} at 400 V, 50 Hz 36 kA

Overload release current setting 320-400 A

Adjustment range undelayed short-circuit release 2000-4000 A

Device construction Built-in device fixed built-in technique

Integrated earth fault protection No

Type of electrical connection of main circuit Screw connection

Suitable for DIN rail (top hat rail) mounting No

DIN rail (top hat rail) mounting optional No

Number of auxiliary contacts as change-over contact 2

With switched-off indicator Yes

With integrated under voltage release Yes

Number of poles 4

Position of connection for main current circuit Front side
Type of control element Wing knob
Complete device with protection unit Yes
Motor drive integrated No
Motor drive optional Yes
Degree of protection (IP) IP30
ETIM for 422011 Low-voltage industrial controls and switchgear (EC000228)
Feature Name
Feature Value
Degree of protection (IP) (EF005474)
IP30
Number of auxiliary contacts as change-over contact (EF003531)
2
Adjustment range undelayed short-circuit release (EF007131)
2000 A
Integrated earth fault protection (EF007296)
No
With integrated under voltage release (EF001390)
Yes
Suitable for DIN rail (top hat rail) mounting (EF007250)
No
Device construction (EF008240)
Built-in device fixed built-in technique
Number of poles (EF001391)
4
Type of electrical connection of main circuit (EF006819)
Screw connection
Overload release current setting (EF002336)
32...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 422011 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.