

**INDUSTRIAL COMPONENT DATA**

# 422080 LEGRAND DPX3 630 ELECT. 3P 630A 70kA

Brand: LEGRAND | Manufacturer Part Number: 422080



|                 |                                                                   |
|-----------------|-------------------------------------------------------------------|
| Manufacturer    | LEGRAND                                                           |
| MPN / Reference | 422080                                                            |
| Catalog number  | 422080                                                            |
| Category        | Power circuit-breaker for trafo/generator/installation protection |
| Minimum order   | 1 Pcs                                                             |
| Document ID     | EO-8C648896BA                                                     |
| Generated       | 2026-08-03                                                        |

## Product Overview

DPX3 630 ELECT. 3P 630A 70kA

MCCB DPX<sup>3</sup> 630 - S2 electronic release - 3P - Icu 70 kA (400 V~) - In 630 A

Automatic MCCB DPX<sup>3</sup> 630 - electronic S2 - 3P - 70kA - 630A

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path      **LEGRAND > DPX3 MOLDED BOX**

## Additional Product Information

Pack (number of units)1

Volume (dm3)10.00

Weight (g)5 932.00

Product characteristicsMCCBs electronic release S2 - fixed version

Adjustment of Ir, Isd, tr, tsd

Instantaneous protection If = 5 kA

Green indicator lamp

Connector for test unit

Logic and dynamic selectivity

4P version: adjustment of neutral on front panel

Breaking capacity Icu 70 kA (400 V~)

3P

In : 630 A

General characteristicsDPX<sup>3</sup> 630 - S2 electronic release MCCBs from 250 to 630 AMoulded case MCCBs for switching,

control isolation and protection of low voltage electrical lines

Can be fitted with auxiliaries

Can be used with earth leakage modules or with residual current relays

Supplied complete with:fixing screws

connection plates for bars

insulated shields (phase barriers)

Conform to IEC 60947-2 - Sealable adjustment

Can be mounted on plate in XL<sup>3</sup> cabinets and enclosures

ETIM for 422080 Low-voltage industrial controls and switchgear (EC000228)

Feature Name

Feature Value

Degree of protection (IP) (EF005474)

IP30

Number of auxiliary contacts as change-over contact (EF003531)

2

Adjustment range undelayed short-circuit release (EF007131)

5000 A

Integrated earth fault protection (EF007296)

No

With integrated under voltage release (EF001390)

Yes

Suitable for DIN rail (top hat rail) mounting (EF007250)

No

Device construction (EF008240)

Built-in device fixed built-in technique

Number of poles (EF001391)

3

Type of electrical connection of main circuit (EF006819)

Screw connection

Overload release current setting (EF0023...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 422080 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.