

## INDUSTRIAL COMPONENT DATA

## 422217 LEGRAND DPX3-I 630 INTER. 3P 630A

Brand: LEGRAND | Manufacturer Part Number: 422217



|                 |                     |
|-----------------|---------------------|
| Manufacturer    | LEGRAND             |
| MPN / Reference | 422217              |
| Catalog number  | 422217              |
| Category        | Switch disconnecter |
| Minimum order   | 1 Pcs               |
| Document ID     | EO-EFDFBC5E7E       |
| Generated       | 2026-07-29          |

## Product Overview

DPX3-I 630 INTER. 3P 630A

DPX<sup>3</sup>-I 630 3 Pole 630A Trip-Free SwitchDPX<sup>3</sup> -I 630 Free Disconnect Switch - 3P - 630A

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification &amp; Catalog Path

Catalog path LEGRAND &gt; DPX3 MOLDED BOX

## Additional Product Information

Version as main switch Yes

Version as maintenance-/service switch Yes

Version as safety switch Yes

Version as emergency stop installation Yes

Version as reversing switch No

Max. rated operation voltage Ue AC 690 V

Rated operating voltage 220-690 V

Rated permanent current Iu 630 A

Rated permanent current at AC-21, 400 V 630 A

Rated short-time withstand current Icw 8 kA

Rated operation power at AC-23, 400 V 252 kW

Conditioned rated short-circuit current Iq 7.6 kA

Number of poles 3

Number of auxiliary contacts as change-over contact 2

Motor drive optional Yes  
Motor drive integrated No  
Voltage release optional Yes  
Device construction Built-in device fixed built-in technique  
Suitable for floor mounting Yes  
Suitable for front mounting 4-hole No  
Suitable for front mounting centre No  
Suitable for distribution board installation Yes  
Suitable for intermediate mounting No  
Colour control element Grey  
Type of control element Wing knob  
Interlockable Yes  
Type of electrical connection of main circuit Screw connection  
Degree of protection (IP), front side IP30  
ETIM for 422217 Low-voltage industrial controls and switchgear (EC000216)  
Feature Name  
Feature Value  
Version as safety switch (EF006985)  
Yes  
Version as maintenance-/service switch (EF006986)  
Yes  
Max. rated operation voltage Ue AC (EF007355)  
690 V  
Version as main switch (EF006981)  
Yes  
Number of auxiliary contacts as change-over contact (EF003531)  
2  
Interlockable (EF006281)  
Yes  
Rated short-time withstand current Icw (EF007050)  
8 kA  
Volta...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 422217 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.