

INDUSTRIAL COMPONENT DATA

422219 LEGRAND DPX3-I 630 INTER. 4P 630A

Brand: LEGRAND | Manufacturer Part Number: 422219



Manufacturer	LEGRAND
MPN / Reference	422219
Catalog number	422219
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-275723E56C
Generated	2026-07-29

Product Overview

DPX3-I 630 INTER. 4P 630A

DPX³-I 630 4 Pole 630A Trip-Free SwitchDPX³ -I 630 Free Disconnect Switch - 4P - 630A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LEGRAND > DPX3 MOLDED BOX

Additional Product Information

Version as main switch Yes

Version as maintenance-/service switch Yes

Version as safety switch Yes

Version as emergency stop installation Yes

Version as reversing switch No

Max. rated operation voltage Ue AC 690 V

Rated operating voltage 220-690 V

Rated permanent current Iu 630 A

Rated permanent current at AC-21, 400 V 630 A

Rated short-time withstand current Icw 8 kA

Rated operation power at AC-23, 400 V 252 kW

Conditioned rated short-circuit current Iq 7.6 kA

Number of poles 4

Number of auxiliary contacts as change-over contact 2

Motor drive optional Yes
Motor drive integrated No
Voltage release optional Yes
Device construction Built-in device fixed built-in technique
Suitable for floor mounting Yes
Suitable for front mounting 4-hole No
Suitable for front mounting centre No
Suitable for distribution board installation Yes
Suitable for intermediate mounting No
Colour control element Grey
Type of control element Wing knob
Interlockable Yes
Type of electrical connection of main circuit Screw connection
Degree of protection (IP), front side IP30
ETIM for 422219 Low-voltage industrial controls and switchgear (EC000216)
Feature Name
Feature Value
Version as safety switch (EF006985)
Yes
Version as maintenance-/service switch (EF006986)
Yes
Max. rated operation voltage Ue AC (EF007355)
690 V
Version as main switch (EF006981)
Yes
Number of auxiliary contacts as change-over contact (EF003531)
2
Interlockable (EF006281)
Yes
Rated short-time withstand current Icw (EF007050)
8 kA
Volta...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 422219 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.