

INDUSTRIAL COMPONENT DATA

422608 LEGRAND DPX3 630 ELE SM 3P 320A 36KA

Brand: LEGRAND | Manufacturer Part Number: 422608



Manufacturer	LEGRAND
MPN / Reference	422608
Catalog number	422608
Category	Power circuit-breaker for trafo/generator/installation protection
Minimum order	1 Pcs
Document ID	EO-2B8BC860EB
Generated	2026-08-03

Product Overview

DPX3 630 ELE SM 3P 320A 36KA

DPX³ 630 Molded Box Switch - Magnetic Only Electronic - 3P - Icu 36 kA (400 V~) - In 320 ADPX³ 630 Molded Case Switch - Electr Magnetic Only - 3P - 36kA - 320A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LEGRAND > DPX3 MOLDED BOX

Additional Product Information

Product features

Magnetic Single Electronic Molded Boxing Switch - Magnetic Adjustable up to 10In - Cutting Power Icu 36 kA (400 V~) - 3P

- In: 320 A General features

DPX³ 630 molded box switches from 250 to 630 A - Automatic power in molded box for cutting, controlling, sectioning and protection of low voltage power lines - Mounted on mounting plate in XL³ boxes and cabinets - Equipped with auxiliaries -

Associated with differential blocks or differential relay - Include connections for bars, screw cover - Comply with UNE-EN

60947-2 - Sealable settings

ETIM for 422608 Low-voltage industrial controls and switchgear (EC000228)

Feature Name

Feature Value

Degree of protection (IP) (EF005474)

IP30

Number of auxiliary contacts as change-over contact (EF003531)

2

Adjustment range undelayed short-circuit release (EF007131)
5000 A
Integrated earth fault protection (EF007296)
No
With integrated under voltage release (EF001390)
Yes
Suitable for DIN rail (top hat rail) mounting (EF007250)
No
Device construction (EF008240)
Built-in device fixed built-in technique
Number of poles (EF001391)
3
Type of electrical connection of main circuit (EF006819)
Screw connection
Overload release current setting (EF002336)
0 A
Motor drive integrated (EF006697)
No
Adjustment range short-term delayed short-circuit release (EF007129)
480 A
Type of control element (EF006976)
Toggle
Rated short-circuit breaking capacity Icu at 400 V, 50 Hz (EF007048)
36 kA
Rated permanent current Iu (EF001389)
320 A
With sw...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 422608 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.