

**INDUSTRIAL COMPONENT DATA**

# 422618 LEGRAND DPX3 630 SM 4P 400A 70KA

Brand: LEGRAND | Manufacturer Part Number: 422618



|                 |                                                                   |
|-----------------|-------------------------------------------------------------------|
| Manufacturer    | LEGRAND                                                           |
| MPN / Reference | 422618                                                            |
| Catalog number  | 422618                                                            |
| Category        | Power circuit-breaker for trafo/generator/installation protection |
| Minimum order   | 1 Pcs                                                             |
| Document ID     | EO-EFBC59944C                                                     |
| Generated       | 2026-07-31                                                        |

## Product Overview

DPX3 630 SM 4P 400A 70KA

DPX<sup>3</sup> 630 molded box switch - magnetic only - 4P - Icu 70 kA (400 V~) - In 400 A

DPX<sup>3</sup> 630 Molded Case Switch - Magnetic Only - 4P - 70kA - 400A

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path      LEGRAND &gt; DPX3 MOLDED BOX

## Additional Product Information

**Product features**

Magnetic only molded box switch - Magnetic adjustable up to 10In - Cutting power Icu 70 kA (400 V~) - 4P - In: 400 A

**General features**

DPX<sup>3</sup> 630 molded box switches from 250 to 630 A - Automatic power in molded box for cutting, controlling, sectioning and protection of low voltage power lines - Mounted on mounting plate in XL<sup>3</sup> boxes and cabinets - Equipped with auxiliaries - Associated with differential blocks or differential relay - Include connections for bars, screw cover - Comply with UNE-EN 60947-2 - Sealable settings

ETIM for 422618 Low-voltage industrial controls and switchgear (EC000228)

Feature Name

Feature Value

Degree of protection (IP) (EF005474)

IP30

Number of auxiliary contacts as change-over contact (EF003531)

2

Adjustment range undelayed short-circuit release (EF007131)  
2000 A  
Integrated earth fault protection (EF007296)  
No  
With integrated under voltage release (EF001390)  
Yes  
Suitable for DIN rail (top hat rail) mounting (EF007250)  
No  
Device construction (EF008240)  
Built-in device fixed built-in technique  
Number of poles (EF001391)  
4  
Type of electrical connection of main circuit (EF006819)  
Screw connection  
Overload release current setting (EF002336)  
0 A  
Motor drive integrated (EF006697)  
No  
Type of control element (EF006976)  
Toggle  
Rated short-circuit breaking capacity Icu at 400 V, 50 Hz (EF007048)  
70 kA  
Rated permanent current Iu (EF001389)  
400 A  
With switched-off indicator (EF007006)  
Yes  
Motor drive optional (EF007386)  
Yes  
Position of connect...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 422618 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.