

INDUSTRIAL COMPONENT DATA

422619 LEGRAND DPX3 630 SM 4P 630A 70KA

Brand: LEGRAND | Manufacturer Part Number: 422619



Manufacturer	LEGRAND
MPN / Reference	422619
Catalog number	422619
Category	Power circuit-breaker for trafo/generator/installation protection
Minimum order	1 Pcs
Document ID	EO-799211D3A7
Generated	2026-08-01

Product Overview

DPX3 630 SM 4P 630A 70KA

DPX³ 630 Molded Box-Switch - Magnetic Only - 4P - Icu 70 kA (400 V~) - In 630 A

DPX³ 630 Molded Case Switch - Magnetic Only - 4P - 70kA - 630A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **LEGRAND > DPX3 MOLDED BOX**

Additional Product Information

Product features

Magnetic only molded box switch - Magnetic adjustable up to 10In - Icu cutting power 70 kA (400 V~) - 4P - In: 630 A

General features

DPX³ 630 molded box switches from 250 to 630 A - Automatic power in molded box for cutting, controlling, sectioning and protection of low voltage power lines - Mounted on mounting plate in XL³ boxes and cabinets - Equipped with auxiliaries - Associated with differential blocks or differential relay - Include connections for bars, screw cover - Comply with UNE-EN 60947-2 - Sealable settings

ETIM for 422619 Low-voltage industrial controls and switchgear (EC000228)

Feature Name

Feature Value

Degree of protection (IP) (EF005474)

IP30

Number of auxiliary contacts as change-over contact (EF003531)

2

Adjustment range undelayed short-circuit release (EF007131)
3150 A

Integrated earth fault protection (EF007296)
No

With integrated under voltage release (EF001390)
Yes

Suitable for DIN rail (top hat rail) mounting (EF007250)
No

Device construction (EF008240)
Built-in device fixed built-in technique

Number of poles (EF001391)
4

Type of electrical connection of main circuit (EF006819)
Screw connection

Overload release current setting (EF002336)
0 A

Motor drive integrated (EF006697)
No

Type of control element (EF006976)
Toggle

Rated short-circuit breaking capacity Icu at 400 V, 50 Hz (EF007048)
70 kA

Rated permanent current Iu (EF001389)
630 A

With switched-off indicator (EF007006)
Yes

Motor drive optional (EF007386)
Yes

Position of connect...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 422619 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.