

INDUSTRIAL COMPONENT DATA

423989 LEGRAND DPX3250HP SM 4P 50A 100KA

Brand: LEGRAND | Manufacturer Part Number: 423989



Manufacturer	LEGRAND
MPN / Reference	423989
Catalog number	423989
Category	Power circuit-breaker for trafo/generator/installation protection
Minimum order	1 Pcs
Document ID	EO-A4879E0DFD
Generated	2026-08-03

Product Overview

DPX3250HP SM 4P 50A 100KA

DPX³250 HP magnetic release only for motor protection - breaking capacity 100kA - 4P - 50A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LEGRAND > DPX3 MOLDED BOX

Additional Product Information

Pack (number of units)O/R

Volume (dm³)O/R

Weight (g)O/R

Product characteristicsDPX³ 250 HP

Magnetic adjustable from 6 to 14 In

Can be mounted on plate in XL³ and XL³ S cabinets and enclosures

Breaking capacity Icu 100 kA (400 V~)

4P

In : 50 A

General characteristicsDPX³ magnetic release only - MCCBs from 16 to 1250 A for motor protectionMoulded case MCCBs for switching, control isolation and protection of three-phase motors

Can be fitted with auxiliaries

Supplied with: screws for connections, fixing screws and insulated shields (phase barriers)

Conform to IEC 60947-2

ETIM for 423989 Low-voltage industrial controls and switchgear (EC000228)

Feature Name
Feature Value
Degree of protection (IP) (EF005474)
IP30
Number of auxiliary contacts as normally open contact (EF001376)
0
Number of auxiliary contacts as change-over contact (EF003531)
2
Number of auxiliary contacts as normally closed contact (EF001377)
0
Adjustment range undelayed short-circuit release (EF007131)
300 A
Integrated earth fault protection (EF007296)
No
With integrated under voltage release (EF001390)
No
Suitable for DIN rail (top hat rail) mounting (EF007250)
No
Device construction (EF008240)
Complete device in housing
Number of poles (EF001391)
4
Type of electrical connection of main circuit (EF006819)
Bolt connection
Motor drive integrated (EF006697)
No
Type of control element (EF006976)
Toggle
Rated short-circuit breaking capacity Icu at 400 V, 50 Hz (EF007048)
100 kA
Rated permanent current Iu (EF001389)
50...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 423989 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.