

## INDUSTRIAL COMPONENT DATA

## 424100 LEGRAND DSX TSE DIN SWITCH 3P 32A

Brand: LEGRAND | Manufacturer Part Number: 424100



|                 |                     |
|-----------------|---------------------|
| Manufacturer    | LEGRAND             |
| MPN / Reference | 424100              |
| Catalog number  | 424100              |
| Category        | Switch disconnecter |
| Minimum order   | 1 Pcs               |
| Document ID     | EO-BBC81E1BEF       |
| Generated       | 2026-08-02          |

## Product Overview

DSX TSE DIN SWITCH 3P 32A

DSX TSE DIN - 32A - 3P network inverter - front direct control - black handle

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification &amp; Catalog Path

Catalog path LEGRAND &gt; INDUSTRIAL CONTACTORS / SWITCHES

## Additional Product Information

DSX TSE DIN - 32A - 3P network inverter - Width: 6 modules - Front direct control - Black handle - Internal mechanism independent of the rotation speed of the handle - Use category AC23 A/B (415V ~) - Remote with lock possibility by padlock in open position (padlock ? 6mm) - Bracket terminals - Accepts copper and aluminum cables - Can be equipped with up to 4 auxiliary contacts (Ref 424208), 2 contacts on each side. Running as a main switch Yes

Operation as a maintenance/repair switch Yes

Operation as a safety switch Yes

Execution as an emergency stop device Yes

Execution as a switch-inverter No

Number of switches 2

Maximum Rated Operating Voltage Ue AC 690 V

Permanent nominal current Iu 32 A

Permanent current assigned to AC-23, 400 V 32 A

Permanent current assigned with AC-21, 400 V 32 A

Icw short-duration rated current resistance 1.5 kA

Rated operating power at 400V AC-23 12.8 kW

Conditional Short-Circuit Current Rating Iq 3 kA  
Number of poles 3  
Number of auxiliary contacts normally closed 4  
Number of auxiliary contacts normally open 4  
Optional motorized drive No  
Integrated motorized drive No  
Optional Tension Release No  
Device construction Fixed integrated technology for integrated device  
Floor Mount No  
Suitable for 4-hole front mounting No  
Suitable for center front mounting No  
Suitable for distributor installation Yes  
Execution of the actuator element Rotary knob (knob)  
Interlockable No  
Main Current Circuit Connection Type Cable clamp  
Degree of protection (IP), front IP20....

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 424100 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.