

INDUSTRIAL COMPONENT DATA

603022 LEGRAND ICP-M P+N 20A

Brand: LEGRAND | Manufacturer Part Number: 603022



Manufacturer	LEGRAND
MPN / Reference	603022
Catalog number	603022
Category	Miniature circuit breaker (MCB)
Minimum order	5 Pcs
Document ID	EO-854767EF15
Generated	2026-07-31

Product Overview

ICP-M P+N 20A

ICP-M - Switch power control 1 P + N - 230 V~ - 20 A - 2 mód.

ICP-M - Power control switch 1 P + N - 230V~ - 20A - 2mod

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LEGRAND > TERTIARY CIRCUIT BREAKERS

Additional Product Information

Product features

Wattage control switch (ICP-M single-Pole + neutral 230 V~ - Curve ICP-M - rated current: 20 - Number of modules: 2

General characteristics

Switch power control to 50A curve ICP-M - circuit Breakers residual current protection - Curve ICP-M according to UNE 20317 - Power of court to 6000A according to UNE 20317 - Use: Switch for Power Control of the subscriber captive Screws

Portaetiquetas incorporated

ETIM for 603022 Circuit breakers and fuses (EC000042)

Feature Name

Feature Value

Explosion-proof (EF004663)

No

Degree of protection (IP) (EF005474)

IP20

Rated short-circuit breaking capacity Icn according to EN 60898 at 230 V (EF009556)

6 kA
Concurrently switching neutral conductor (EF005997)
Yes
Voltage type (EF000187)
AC
Additional equipment possible (EF008148)
Yes
Rated impulse withstand voltage Uimp (EF011980)
4 kV
Number of protected poles (EF005548)
1
Frequency (EF000416)
50 Hz
Built-in depth (EF000218)
44 mm
Number of poles (total) (EF008618)
2
Pollution degree (EF002570)
2
Width in number of modular spacings (EF002950)
35.6
Rated insulation voltage Ui (EF001366)
500 V
Over voltage category (EF002569)
3
Rated current (EF000227)
20 A
Current limiting class (EF002568)
3
Flush-mounted installation (EF007517)
Yes
Release characteristic (EF000889)
Other
Rated voltage (EF000228)
230 V

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 603022 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.